

Wehsite



Facehook



Voutuh

Copy Right Jan 2017 V1.0
All Rights Reserved By
Fenixlight Limited

FENIXLIGHT **LIMITED**

Tel: +86-755-29631163/83/93 Fax: +86-755-29631181 Email: info@fenixlight.com www.fenixlight.com Address: 8/F, 2nd Building, DongFangMing Industrial Center, 33rd District, Bao'an, Shenzhen 518133, China





Illuminate Your Adventure



TO BE THE BEST OUTDOOR SPORT LIGHTING BRAND IN THE WORLD

Fenix is a leading outdoor sport lighting brand as well as a China national high-tech enterprise, specializing in R&D, manufacturing and selling of outdoor sport lighting tools, including mid/high-end flashlights, headlamps, bicycle lights, camping lanterns as well as accessories. Fenix products are now being sold in more than 100 countries around the world.

Concentrating on innovative lighting technology and solutions, Fenix constantly develops LED lighting tools of high performance and high reliability, satisfying customers' pursuit of versatile illumination tools of high quality through exquisite craftsmanship. Fenix's products are widely used in the fields of outdoor sport, industry, law enforcement, military, edc (everyday carry), etc. As every product is released with excellent performance and reliable quality, Fenix has become known worldwide as a premium LED lighting brand.

Committed to the mission of innovating outdoor sport lighting and to make users' experience as pleasant as possible, Fenix aims to be the best outdoor sport lighting brand in the world.

ABOUT FENIX

BRAND ORIGIN

As the great Chinese thinker Lu Xun said: "Improvement roots from dissatisfaction". The establishment of Fenix also roots from dissatisfaction. A group of young men, passionate about high quality illumination tools but unsatisfied with lighting products at that time, set out to make perfect flashlights, endeavoring to make the best flashlights in the world.

Adhering to the concept of "providing excellent products to customers through innovative design", Fenix has grown up to become a world-renowned outdoor sport lighting brand!

BRAND CONNOTATION

The word Fenix roots from the English word phoenix [fi:niks], which in the Chinese translation means "phoenix" or "perfect thing", and the phoenix figure represents luck, blessedness and perfection in the Chinese culture.

FENIX'S AWARDS

- Flashlight of 2005
- National High-Tech Enterprise
- The "Best in Show" Award in 2011 Outdoor Retailer Trade Show
- The LD20 got the title: "Best LED Flashlight"
- 2011 2013 "Zunlv Award" during annual election of Chinese outdoor industry awards
- The "Best of Show" Award AFTA Trade Show 2013
- PD12 ISPO "Award Winner" 2013/2014
- Named: The Best Cycling Gear of 2013 by Outside magazine
- CL20 ISPO "Award Winner" 2015/2016
- "Editor's Choice" award by Outdoor Life magazine
- Single product "Brand of the Year" 2013
- BT20 ISPO Asia Products "Gold Winner" Award 2012/2013
- Silver Prize in Asia Outdoor Industry Awards
- Named "Best Bargain" by Backpacker magazine
- Silver Prize in Chinese Outdoor Gear Award
- Named as one of the "Top 10 Travel Gadgets under \$50" by New York Times newspaper
- BC30R Silver Award in Asia Outdoor Industry Awards; ISPO Asia Products "Gold Winner" Award 2015/2016
- CL25R—ISPO(Asia) Award Gold Winner
- HL10 2016—ISPO Global Product Winner



















INDEX

TK series Tough and powerful flashlights	7
PD series Portable and high-intensity flashlights	17
LD series Professional outdoor flashlights	23
E series Outdoor flashlights	25
MC series Angle lights	3!
FD series Adjustable focus lights	37
RC/UC series High-performance rechargeable flashlights	41
SD series Underwater sport lights	51
HP series High performance outdoor headlamp	5!
HL series Lightweight outdoor headlamps	61
Bicycle light	69
Camping lantern	_
Accessories	81

HIGH PERFORMANCE AND RELIABLE OUTDOOR SPORT LIGHTING TOOLS

HIGH PERFORMANCE

Fenix utilizes the most advanced, world-class LED's with a lifespan of 50,000 hours, leading the trend in the LED industry and staying up to date with development in the LED industry. Owing to the accumulative experience of the diligent R&D team, Fenix is able to make the most of high photoelectric conversion efficiency, to have limited electric energy transformed into light energy, plus the choice of professional ultra-clear glass lens with anti-reflective coating, so that each spectral LED is effectively emitted. Additionally, outstanding constant current circuitry highlights Fenix's products, meaning a constant bright light with no flickering as the batteries discharge.

Digital regulation, constant brightness

High-efficiency optical system

HIGH RELIABILITY

Fenix abides by the ISO9001 quality control system, which strictly supervises material selection, product manufacturing and quality inspection. As a member of PLATO, Fenix always sticks with professional inspection equipment and conducts every test in accordance with ANSI standards. Reliable structure design empowers Fenix lighting tools with great heat dissipation, extra strong dust resistance and waterproof capability to face various environments. Most of Fenix's products are waterproof to IPX8 standard; the diving flashlight is even waterproof to 100 meters deep.



PROMINENT OPTICAL SYSTEM

Sparing no efforts in meeting different environmental conditions, Fenix focuses on light color and light spot design, thus making every Fenix product balanced in terms of output, distance and beam angle, and reliable enough for various demanding applications. Fenix continues searching for a breakthrough - some products have orange-peel reflectors for ideal lighting efficacy; some have dual light sources to allow for spot- and floodlight needs; some even have composite reflectors for choosing multiple light colors. Fenix bicycle lights feature Dual Distance Beam System which is greatly favored by users and has received major industry awards.

Utilizing the latest LED

ADVANCED LIGHTING TECHNOLOGY

EXQUISITE WORKMANSHIP


Constant current circuitry

The application of advanced LED's and optical devices provide the foundation of manufacturing high-performance products. The critical fact that Fenix is greatly favored comes from manufacturing excellence and quality requirements. Fenix insists on aircraft-grade aluminum material to be produced by computerized numerical control (CNC) machinery, and premium Type III hard-anodized anti-abrasive finishing ensures Fenix products are sturdy and durable. Furthermore, exterior structure and surface processing is not the only and end result. Fenix commits to excellence also in circuit design, an independent yet advanced SMT product line, CNC product line and oxygen installation, which all ensure that every product is refined internally as well as externally.

UNREMITTING INNOVATION

It is deeply believed that innovation is the source of the ongoing progress and development of the Fenix brand. On the one hand, Fenix has exploited the camping lantern, a new product line which enriches Fenix as an all-around outdoor lighting brand. On the other hand, Fenix is committed to developing and introducing new techniques, dedicated to pleasing illumination experience and user-friendliness. The four-proofing headlamps even lead the trend in high-performance headlamps, and the characteristic cold-resistant camping lantern act tough in harsh environments.

ILLUMINATE YOUR ADVENTURE



HIKING

For a night of hiking, lightweight lighting tools are usually sufficient for common users. A long battery life and $\ up\ close\ illumination\ are\ bonus\ points.\ For\ team\ leaders\ though,\ this\ kind\ of\ flashlight\ is\ not\ suitable.\ For$ them lighting tools with ultra-high output and far-reaching beam are more important than long duration, because they always have to plan and "read" the road ahead.

Some recommended Fenix models: PD35, LD22, LD12, E12, UC30, HL60R, HL30, HL23, HL10

Generally a high output lighting tool is not required for camping activities. A useful light would be one with a lood beam capable of lighting a large area for a long time, thus a lantern that can run all night without the need of a battery replacement would be considered ideal, without being too expensive.

Some recommended Fenix models: TK47, TK47UE, FD30, CL30R, CL25R, CL20, CL05

CLIMBING

When climbing, a lighting tool with a soft flood beam is really helpful, especially when rock climbing or in snowy environments. Better color rendering makes for better user experience. For higher altitude climbing a cold-resistant lighting tool is particularly important - not only for better reliability, but also to maintain a longer duration of light.

Some recommended Fenix models: HL55, HL50, HP12, HL23, HP15UE

safety is of utmost importance, so choose a reliable tool as companion. Some recommended Fenix models: HL60R, HL50, HL26R, HL15, HL10

High speed cross-country cycling requires a bicycle light with high output, combined with long-distance and brighter light conditions, an economical bicycle light with fast and convenient dismounting are better than

those with a higher output.
Some recommended Fenix models: BC30R, BC30, BC21R

A flashlight used for hunting should have a high output with a spotlight to ensure optimal beam distance, but because the light will be used only occasionally while hunting, a long runtime is not a huge requirement. Generally a hunting flashlight will need accessories that can absorb the recoil of a gun. Lights preferred for hunting are those that are equipped with red lights, or where a red filter can be added. Some recommended Fenix models: TK20R, TK32, TK16, TK09, FD41, FD30

While fishing, lighting tools will also be used only occasionally, thus long duration is not important. Fish are usually attracted by blue light, so lighting tools with blue lights are made for fishing. Some recommended Fenix models: HP40F, HL55, HL60R, HP15UE

SEARCHING

Lighting tools for searching will demand high output and ultra-long beam distance, but these lighting tools are also burdened with larger volume and larger weight. Both these factors though, are secondary to the high performance of these lighting tools Some recommended Fenix models: TK47, TK47UE, FD41,TK20RTK75, RC40, TK35UE, HP30R, HP25R,

LIVE FOR OUTDOORS

EMERGENCY RESCUE

Nowadays, people (personal and families) pay more attention to emergency lighting tools, let alone those professional security organizations that need high-performance lighting tools. During emergency rescue operations, readily accessible batteries like AA and CR123A really matter, so lighting tools compatible with these kinds of batteries are greatly preferred.

Some recommended Fenix models: LD22, PD35, RC20, UC35, HL55, HL60R, TK75, TK35UE,

LAW ENFORCEMENT/TACTICAL

First and foremost, high-output spotlights and far-reaching beams are indispensable features for flashlights used for law enforcement and tactical operations. Besides that, certain unique tactical features cannot be neglected, such as tactical switches, strike crown bezels, grip rings and strobe functions. Compatibility with other accessories used for tactical applications, like tactical flashlight rings, remote pressure switches and

traffic wands, is also very important.

Some recommended Fenix models: TK16, PD35, PD35 Tac, PD32, UC35, TK20R, TK15UE, FD41, FD30

For insuring your safety, the lighting tools you use should have high output, while some tactical requirements are a strike bezel and strobe function. Furthermore, this kind of lighting tool should be highly reliable in resisting dust, water and shocks, and should be tough enough to confront emergency conditions. Some recommended Fenix models: RC20, TK16, PD35, PD35 Tac, UC35, HP15UE, TK20R, TK15UE,

Some recommended Fenix models: TK35, TK35UE, LD41, HL55, HL60R, HP25, HP12, HP15UE, TK20R, TK47, TK47UE, FD30

not of great importance due to the buoyancy provided by water. Some recommended Fenix models: SD11, SD20

INDUSTRIAL WORKPLACE

Rechargeable lighting products are usually warmly welcomed by industrial workers because of economic practicality. These rechargeable lights should feature multiple output selection and fast and convenient operation, while at the same time have high waterproofing capabilities, and be shock- and dust resistant. All these elements combined, react tough against the complex environments of industrial workplaces. Some recommended Fenix models: RC20, RC11, RC09, UC30, UC35, HP15UE, FD41, HL60R

PHOTOGRAPHY

Convenience and portability are essential for photography, where it is sometimes necessary to have manmade light, e. g. during nighttime outdoor photography. A helpful lighting tool brings about the best photographic works. For these photographic activities, features that are essential are neutral white lights for better color rendering, multiple output choices, and the flexibility to adjust between spot- and floodlight, plus the option to add colored filter adapters when needed. Some recommended Fenix models: LD75C, TK35UE, TK75, HL50, HL55, FD41, FD30, SD11

EDC (Everyday carry) as the name suggests, is designed to be carried with you all the time - to be a part of your daily life, thus this kind of lighting tool needs to be ultra-compact, and in critical emergency situations can help to save lives. Precise circuit design gives regulated low output with long lasting duration, and because a choice of output levels is not essential, two or three output selections should be sufficient. In cases of emergency, remember that this little buddy will always be by your side.

Some recommended Fenix models: E01, E05, E12, E15, LD09, HL05, CL05, UC02, UC02SS, UC01















- 4000 lumens output
- User-friendly interface
- Battery level indication
- Lockout switch against accidental activation
- Tripod socket



52.5mm (2.0 in) Head diameter: 87.5mm (3.4 in)

WEIGHT: 575g (20.2 oz) excluding battery

The TK75, an astonishing combination of 4000 lumens maximum output and more than 11 days runtime. Versatile and all-powerful, this flashlight satisfies demands during searching, securing, caving and more.

Dual body switches offer user-friendly output selection of 4 brightness levels and 2 momentary on modes, while the lockout function prevents the possibility of unintended operation of the flashlight. Additionally, a built-in socket that can take either a shoulder strap or tripod mount for carrying or mounting, makes the TK75 even more advantageous and reliable.

	ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTAN	T WATERPROOF				
TURBO	4000 Lumens	1h 40min	650m	105600cd						
HIGH	1600 Lumens	3h 40min	422m	44600cd		IP68, underwater 2m				
MED	600 Lumens	11h 20min	257m	16500cd	1m					
LOW	35 Lumens	270h	65m	1050cd						
STROBE	4000 Lumens	/	/	/						

Max 3200 Lumens

- Cree XHP70 LED, high output and long distance beam
- Catapult assisted belt clip
- Dual switch operation, momentary-on strobe
- Waterproof Micro USB fast charging port



SIZE: Length: 270mm(10.6 in) Head diameter: 61.5mm(2.4 in) Body diameter: 36.5mm(1.4 in) WEIGHT: 396g (14.0 oz) excluding battery

Fenix TK65R is a high-performance flashlight which can be widely used in security and safety, policing and law enforcement tasks. This tough flashlight features durable structure and powerful performance. Fitted with Cree XHP70 LED, TK65R delivers a maximum output of 3200 lumens and a far-reaching beam distance of 375m. The newly designed catapult assisted belt clip and momentary-on strobe function let users quickly detach the flashlight to access and activate the strobe. IP68 rated structure makes TK65R fearless of any environment and

In addition, the Micro USB fast charging port in the light's tail and the included 10000mAh Li-ion battery strengthen TK65R into a highly efficient power source and efficient power usage.

	ANSI/PLATO FL1								
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
TURBO	3200 Lumens	1h 20min	375m	35000cd					
HIGH	1500 Lumens	4h 20min	217m	12000cd		IP68,			
MED	400 Lumens	11h 25min	139m	4800cd					
LOW	150 Lumens	36h 50min	77m	1500cd	1m	underwater			
ECO	30 Lumens	125h	34m	300cd		2m			
STROBE	3200 Lumens	1	/	/					
sos	400 Lumens	/	/	/					



■ 700 meters neutral white beam

Multi-function tail light

- Dual independent light switches
- Lockout function
- Rugged structure design

SIZE: Length: 266.2mm (10.5 in) Head diameter: 61.5mm (2.4 in) Body diameter: 28.6mm (1.1 in)

WEIGHT: 376g (13.3 oz) excluding batteries











Fenix TK47 is an ultra-long range flashlight innovatively equipped with a multi-functional tail light. The headlight is fitted with the long-range Cree XHP35 HI LED and deep metal reflection cup, resulting in the ultra-long beam of 700 meters, which is beyond the visible limit. While the diffused tail light is fitted with a neutral white light and a red light, which is independently controlled, they are also versatile aids in relaxing, reading, camping or signaling. In addition to searching, caving, hunting, TK47 is also the recommendable spare lighting tool for your self-driving journey.

	ANSI/PLATO FL1										
	MC	DDE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
	G E	TURBO	1300 Lumens	1h 50min	700m	122500cd					
HEADLIGHT	GENER/	HIGH	400 Lumens	7h 15min	412m	42400cd					
	AL M	MED	100 Lumens	40h	214m	11500cd					
E E	MODE	LOW	10 Lumens	220h	73m	1300cd		IP68.			
-	S	STROBE	1300 Lumens	1	1	1	1m	underwater			
TAIL	WH	ITE LIGHT	30 Lumens	43h 30min	*8m	/		2m			
	RI	ED LIGHT	1.5 Lumens	150h	/	/					
LIGHT	RE	D FLASH	1.5 Lumens	1	1	1					
1	R	RED SOS	1.5 Lumens	1	1	1					

^{*}Tail light with a wide-range 8m beam diameter

TK47 Ult

Ultimate Edition
Max 3200 Lumens

- 3200 lumens headlight
- Multi-function tail light
- Dual independent light switches
- Lockout function
- Rugged structure design



NEW

SIZE: Length: 266.2mm(10.5 in) Head diameter: 61.5mm(2.4 in) Body diameter: 28.6mm(1.1 in)

WEIGHT: 365g(12.9 oz) excluding batteries

Fenix TK47UE is a high performance flashlight innovatively equipped with a multi-functional tail light. The headlight is fitted with the high performance Cree XHP70 LED and orange peel reflector cup, resulting in a wide beam up to 3200 lumens and over 400 meters. While the diffused tail light is fitted with a neutral white light and a red light, which is independently controlled, they are also versatile aids in relaxing, reading, camping or signaling. In addition to searching, caving, hunting, TK47UE is also the recommendable spare lighting tool for your self-driving journey.

ANSI/PLATO FL1

	MC	ODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF
	G	ູດ TURBO 3200 Lu	3200 Lumens	1h	408m	41600cd		
픎	GENERAL	HIGH	1000 Lumens	3h 20min	232m	13450cd		
HEADLIGHT		MED	350 Lumens	11h 20min	130m	4200cd		
	MODE	LOW	100 Lumens	46h	69m	1200cd		
=	m	ECO	20 Lumens	170h	31m	240cd	1	IP68,
	STROBE		3200 Lumens	/	/	/	- 1m	underwater 2m
TAIL	WH	IITE LIGHT	30 Lumens	43h 30min	*8m	/		
	RI	ED LIGHT	1.5 Lumens	150h	1	1		
딚	RE	ED FLASH	1.5 Lumens	/	/	/		
<u> </u>	F	RED SOS	1.5 Lumens	1	1	/		

^{*}Tail light with a wide-range 8m beam diameter

TK35 Ultimate Edition
Max 2000 Lumens

- Utilizes CREE XHP50 LED
- Max 2000 lumens output
- 320m far-reaching beam distance
- 5 output levels plus strobe and SOS operated by dual tail switches



SIZE: Length: 161mm (6.3 in) Head diameter: 50mm (2.0 in)

WEIGHT: 240g (8.5 oz) excluding battery

This upgraded flashlight integrates exquisite craftsmanship with high performance. Fitted with a CREE XHP50 LED that emits 2000 lumens; five brightness levels plus Strobe and SOS, but from a more compact body. The dual button tail switch is convenient for fast and simplified operation, allowing for one-handed momentary-on function and mode changing.

Moreover, a paralleled battery compartment and compatibility with both 18650 rechargeable Li-lon and CR123A batteries make this flashlight stand out in outdoor searching, caving, standby application while driving, and more.

	ANSI/PLATO FL1								
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
TURBO	2000 Lumens	1h 15min	320m	25600cd	-				
HIGH	1050 Lumens	3h 10min	231m	13350cd					
MED	380 Lumens	9h 15min	140m	4900cd		IP68.			
LOW	120 Lumens	33h	78m	1520cd	1m	underwater			
ECO	20 Lumens	160h	32m	255cd		2m			
STROBE	2000 Lumens	1	1	1					
sos	380 Lumens	1	1	1					

FK35

Max 960 Lumens



Max 960 lumens output

 Five brightness levels and two flashing modes

Dual tail switches

Integrated flat body design

 Powered by two 18650 or four CR123A batteries

Power switch



Fods TK35

SIZE: Length: 159mm (6.3 in) Body diameter: 43mm (1.7 in) Head diameter: 48mm (1.9 in) WEIGHT: 217g (7.7 oz) excluding battery

The Fenix TK35 is a high-intensity and multi-functional flashlight. Utilizing a CREE XM-L2 U2 LED, it delivers max 960 lumens output from two 18650 batteries or four CR123A batteries. Seven outputs including strobe and SOS are controlled by the dual tail switches. Durable, reliable and balanced for easy carry, the TK35 excels in various outdoor activities, such as exploring, camping, searching, caving and more.

ΔN	ISI/I	ΡΙ Δ	TO	FL1
			•	

MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF
TURBO	960 Lumens	2h	355m	31500cd		
HIGH	400 Lumens	6h 45min	229m	13100cd		IP68.
MED	150 Lumens	21h	140m	4900cd		
LOW	50 Lumens	60h	81m	1640cd	1m	underwater
ECO	8 Lumens	240h	33m	270cd	-	2m
STROBE	960 Lumens	1	1	1		
sos	150 Lumens	1	/	1		

TK32 Max 1000 Lumens

- Tri-color source of white, green and red
- Max 422 meters beam distance
- Dual tactical tail switches
- Fast access to colored light





SIZE: Length: 159mm (6.3 in) Body diameter: 25.4mm (1.0 in) Head diameter: 52mm (2.0 in) WEIGHT: 175g (6.2 oz) excluding battery

The redesigned Fenix TK32 now delivers an output increase to 1000 lumens a long beam throw to 422 meters and a substantial output increase in red and green color lumens. All this wonderful upgrades plus the standard features of four digitally regulated brightness levels cater your versatile situations in hunting. searching and more. The light is also conveniently operated by its tail switch, and is waterproof to the IPX8 standard for water resistance.

	ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
TURBO	1000 Lumens	1h 50min	422m	44500cd		IP68,				
HIGH	350 Lumens	4h 45min	245m	15000cd]					
MED	100 Lumens	15h 25min	138m	4760cd						
LOW	8 Lumens	170h	40m	400cd	1m					
RED HIGH	105 Lumens	4h 15min	65m	1050cd] ""	underwater 2m				
RED LOW	15 Lumens	65h	23m	135cd	- - -					
GREEN HIGH	165 Lumens	5h 30min	105m	2760cd						
GREEN LOW	30 Lumens	40h	45m	505cd						

TK16

Max 1000 Lumens

- Overwhelming output and pocket size
- Dual tactical tail switches
- Reliable dual layer body
- Specialized remote pressure switch



SIZE: Length: 140mm (5.5 in) Body diameter: 25mm (1.0 in) Head diameter: 34mm (1.3 in)

WEIGHT: 122g (4.3 oz) excluding battery

The Fenix TK16 flashlight integrates functionality and performance, empowering it as a reliable and indispensable tool in emergency and tactics. This LED light is the first to feature Fenix new dual tactical tail switches for one-finger operation and instant access to strobe and momentary-on functions. The TK16 delivers four brightness modes, plus strobe, and can throw 1000 lumens of maximum output and far-reaching distance of up to 240 meters. Key design elements include a strike face bezel, grip ring, body clip and the reliable Dual Layer Body.

	ANSI/PLATO FL1									
MODE	ОИТРИТ	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
TURBO	1000 Lumens	1h 10min	240m	14480cd		IP68, underwater 2m				
HIGH	400 Lumens	3h 25min	155m	6000cd						
MED	150 Lumens	10h	97m	2350cd	1m					
LOW	10 Lumens	150h	23m	130cd						
STROBE	1000 Lumens	/	/	1						

TK15 Ultimate Edition Max 1000 Lumens

Two colors for options

Max 325-meter beam distance

Tactical tail switch plus side switch

4 output levels plus Strobe mode

mens Black

SIZE: Length: 142.5mm (5.6 in) Body diameter: 25.4mm (1.0 in) Head diameter: 34mm(1.3 in)

Iron grey

WEIGHT: 141g (5.0 oz) excluding battery

The Fenix TK15UE defines extreme ruggedness. This light employs the new CREE XP-L HI V3 LED technology, which allows the light to throw an impressive beam distance of 325 meters and deliver a maximum output of 1000 lumens. With an impact resistant strike face bezel, the TK15UE is ready for heavy duty action. Complete with a tactical tail switch with momentary capability and a side switch to access four brightness levels and Strobe, this tactical light is built to assist law enforcement, search and rescue, military and more.

	ANSI/PLATO FL1								
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
TURBO	1000 Lumens	2h	325m	26400cd		IP68, underwater 2m			
HIGH	350 Lumens	4h 20min	194m	9400cd	1				
MED	150 Lumens	11h 30min	125m	3900cd	1m				
LOW	10 Lumens	135h	31m	240cd					
STROBE	1000 Lumens	1	/	/					

TK09

Max 900 Lumens

- Pocket-size
- 310 meters far-reaching beam distance
- 900 lumens momentary-on function
- Waterproof to IPX8 standard



SIZE: Length: 130mm (5.1 in) Diameter: 25.4mm (1 in) Head diameter: 34mm (1.3 in)

WEIGHT: 105g (3.7 oz) excluding battery

Fenix'sTK09 upholds the typical design concept of the TK series as being tough, powerful and waterproof, while keeping the simple and compact structure. Using a CREE XP-L HI LED and one 18650 battery, this 130 mm (5.1 in) long body boasts a max 900 lm output and an extended distance of up to 310 m. A tactical tail switch gives instant access to top brightness, and controls the 3 output and strobe. As it stands, the TK09 gives flexibility in law enforcement and hunting tasks, and does not miss a step in frigid environments thanks to compatibility with CR123A batteries.

ANSI/PLATO FL1								
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF		
HIGH	900 Lumens	1h 25min	310m	24000cd	- 1m			
MED	450 Lumens	4h 55min	218m	11850cd		IP68,		
LOW	50 Lumens	37h	72m	1250cd		underwater 2m		
STROBE	900 Lumens	1	/	/				



TK20R

Max 1000 Lumens







- Micro USB rechargeable, inner waterproofing treatment
- Cree XP-L HI V3 LED with 310 meters beam distance
- Reliable dual layer body structure
- Battery level indication

SIZE: Length: 151.5mm(6.0 in) Body diameter: 25mm(1.0 in) Head diameter: 34mm(1.3 in)

WEIGHT: 141g (5.0 oz) excluding battery





Fenix TK20R is a Micro USB rechargeable flashlight that is designed for tactical applications. It delivers a maximum beam distance of 310 meters by utilizing a CREE XP-L HI V3 LED, and has a max output of 1000 lumens. In addition, it is powered by one 18650 rechargeable Li-ion battery, and two cold resistant CR123A can be used as standby batteries. Features are dual layer body, inner waterproofing treatment; and a tactical tail switch and side switch that allow easy access to four output levels and strobe. This compact but hardy flashlight is ideal for tactical application, industrial tasks and hunting.

	ANSI/PLATO FL1												
MODE	OUTPUT	IMPACT RESISTANT	WATERPROOF										
TURBO	1000 Lumens	2h	1h 40min	310m	24000cd								
HIGH	350 Lumens	4h 20min	4h	193m	9310cd		IP68,						
MED	150 Lumens	11h	10h 30min	126m	3970cd	1m	underwater						
LOW	DW 10 Lumens		135h	31m	240cd		2m						
STROBE	1000 Lumens	/	/	/	/								





PD40R

Max 3000 Lumens

Fitted with quad core Cree XHP 70 LED

Included 26650 rechargeable Li-ion power battery

Micro USB rechargeable

Dual switch operation, lockout function

Battery level indication



SIZE: Length: 138.5mm (5.5 in) Body diameter:34mm (1.2 in) Head diameter:30mm (1.3 in)

WEIGHT: 126g (4.4 oz) excluding battery







The super bright Fenix PD40R is now USB rechargeable. It is powered by a 26650 rechargeable power battery, which activates the maximum output of 3000 lumens and extends the runtime dramatically. In addition, the flashlight features digitally regulated output and IPX8 waterproof classification, plus this compact flashlight also offers a comfortable grip. General lighting modes and strobe are independently controlled by the two switches. It will be your trusted companion.

	ANSI/PLATO FL1											
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF						
TURBO	3000 Lumens	12min	200m	10000cd								
HIGH	1000 Lumens	2h	123m	3800cd								
MED	350 Lumens	7h 25min	68m	1150cd		IP68,						
LOW	100 Lumens	21h 15min	39m	380cd	1m	underwater						
ECO	20 Lumens	55h	16m	65cd		2m						
STROBE	1000 Lumens	1	1	/								
sos	350 Lumens	1	/	/								
		· · · · · · · · · · · · · · · · · · ·	I .	1								



PD35

Max 960 Lumens

Cree XM-L 2 (U2) LED, max 960 lumens

- Optimum output-to-weight ratios
- Five brightness levels
- Instant strobe

SIZE: Length: 139mm (5.5 in) Diameter: 25.4mm (1.0 in) WEIGHT: 87g (3.1 oz) excluding battery








change the output. Portable becomes powerful with this go-anywhere, category-changing model from Fenix.





ANSI/PLATO FL1											
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
TURBO	960 Lumens	1h10min	208m	10800cd							
HIGH	460 Lumens	3h15min	133m	4400cd]						
MED	180 Lumens	10h	79m	1550cd] - 1m	IP68,					
LOW	50 Lumens	38h	43m	450cd] ''''	underwater 2m					
ECO	14 Lumens	150h	20m	100cd							
STROBE	960 Lumens	/	/	/							

PD35 TAC Max 1000 Lumens

Cree XP-L LED

Optimum weight-to-output ratios

Tactical Mode

Outdoor Mode



SIZE: Length: 137mm (5.4 in) Head diameter: 25.4mm (1.0 in)

WEIGHT: 89g (3.1 oz) excluding battery







The Fenix PD35 TAC retains the pocket-size of the PD35, but with higher performance, and it focuses on tactical employment. Measuring at less than 14cm long, it features up to 1000 lumens output and a throw distance of 200m. In Outdoor mode it delivers 6 output levels plus a strobe mode. Tactical mode enhances the PD35 TAC with simplified and fast output selection. From daily outdoor lighting to professional law enforcement applications, you can resort to the PD35 TAC with confidence.

	ANSI/PLATO FL1												
MODE	OUTPUT	TACTICAL	OUTDOOR	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
TURBO	1000 Lumens	~	~	1h 10min	200m	10000cd							
HIGH	500 Lumens		~	2h 55min	135m	4550cd							
MED	200 Lumens		~	8h 30min	80m	1600cd	1m	IP68 Underwater					
LOW	60 Lumens	~	~	29h 15min	48m	550cd] ''''	2m					
ECO	8 Lumens		~	140h	17m	70cd]						
STROBE	1000 Lumens	√	√	1	1	1							

Max 900 Lumens

Pocket size

■ High-performance Cree XP-L HI LED

■ Tactical tail switch, stainless steel side switch

Multiple available accessories



SIZE: Length: 129.5mm (5.1 in) Body diameter: 22.6mm (0.9 in) Head diameter: 24mm (0.9 in) WEIGHT: 77g (2.7 oz) excluding battery

If you're not sure what to use to light up the way to your destinations, then choose Fenix's PD32, which is the comprehensive integration of high performance and efficient output in a compact body, as well as long battery duration and far-reaching beam distance. Furthermore, compatibility with an 18650 battery or two CR123A batteries, makes this PD32 ideal in confronting harsh environments. In need of an illuminating tool for specialized applications such as law enforcement and searching and rescuing, let alone outdoor activities like hiking and camping, then look no further than the PD32.

ANSI/PLATO FL1

MODE	ОИТРИТ	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF
TURBO	900 Lumens	1h 55min	240m	14400cd		
HIGH	400 Lumens	4h	156m	6050cd		
MED	150 Lumens	10h 25min	97m	2350cd		IP68.
LOW	50 Lumens	37h 5min	52m	650cd	1m	underwater
ECO	5 Lumens	260h	13m	40cd		2m
STROBE	900 Lumens	1	1	1		
sos	50 Lumens	1	1	1		

Max 550 Lumens

- Cree XP-L LED
- Optimum output-to-weight ratios
- Intelligent drive circuit
- Powered by one 16340 or CR123A battery



SIZE: Length: 93mm (3.7 in) Diameter: 21.5mm (0.8 in) WEIGHT: 47g (1.7 oz) excluding battery

The Fenix PD25 is more powerful than such a tiny flashlight seems. Equipped with Cree XP-L LED and intelligent drive circuit, the flashlight produces 550 lumens stunning output from a 16340 rechargeable Li-ion battery. It's also compatible with CR123A battery. Besides, a tactical tail switch for momentary-on function, a metal side switch on the head are all you need to control five output levels including strobe mode.

ΛN	QI.	/DI	E1	1

MODE	OUT	OUTPUT		RUNTIME		DISTANCE		NSITY	IMPACT RESISTANT	WATERPROOF
IIIODE	CR123A	16340	CR123A	16340	CR123A	16340	CR123A	16340	IIII AOT REGISTANT	WAIER ROOF
TURBO	400 lumens	550 lumens	1h 10min	35min	116m	130m	3360cd	4225cd		
HIGH	150 lumens	150 lumens	3h 15min	2h 25min	71m		1260cd			ID00
MED	50 lumens	50 lumens	9h 5min	7h 10min	41r	41m		0cd	1m	IP68, underwater
LOW	5 lumens	5 lumens	100h	53h	13m		40cd			2m
STROBE	400 lumens	550 lumens	/	/	,	/		/		





SIZE: Length: 158 mm (6.22 in.) Body Diameter: 52 mm (2.04in.) Head Diameter: 74 mm (2.91in.) **WEIGHT:** 430g (15.16 oz) excluding battery







The Fenix LD75C flashlight, with extreme output, compact size plus multi-color LEDs, lights up your favorite outdoors with four color options and seven white output levels. LD75C puts 4200 lumens output with 490 meters throw inside a package less than 16cm long, and can be stowed easily in a backpack, glove compartment, or tool case. The flashlight also features double circuit design and intelligent thermal control for flexible and reliable power use.

	ANSI/PLATO FL1										
	MODE	OUTPUT	RUNTIME	DISTANCE	IMPACT RESISTANT	WATERPROOF					
	TURBO	4000 Lumens	1h 30min	490m	60000cd						
	HIGH	1800 Lumens	3h	296m	21950cd						
	MED	600 Lumens	11h	176m	7755cd		ID00				
	LOW	200 Lumens	35h	100m	2500cd	1					
	ECO	40 Lumens	175h	45m	510cd	1	IP68, underwater				
	STROBE	4000 Lumens	/	/	/	1m	2m				
₹	RED	140 Lumens	14h	24m	145cd						
Multi-col LED	GREEN	190 Lumens	11h	28m	200cd						
	BLUE	45 Lumens	11h	7m	12cd						
red	WHITE	200 Lumens	11h	43m	480cd						

LD41

Max 960 Lumens

- 960 lumens output and 300 meters beam distance
- Compact and flat body design
- 4 brightness levels plus strobe and SOS
- Dual tail switch with momentary-on function



SIZE: Length: 175mm (6.9 in) Diameter: 40mm (1.6 in)

WEIGHT: 190g (6.7 oz) excluding batteries

Featuring max 960 lumens output, LD41 provides four brightness levels plus strobe and SOS modes. With intelligent circuit, rugged metal housing and IPX8 rating, this reliable light is suitable for searching, camping, caving and more.

ANSI/PLATO FL1 OUTPUT RUNTIME DISTANCE IMPACT RESISTANT WATERPROOF MODE INTENSITY TURBO 960 Lumens 300m 22500cd 1h HIGH 400 Lumens 2h 25min 193m IP68, MED 150 Lumens 9h 30min 118m 3480cd underwater LOW 6 Lumens 200h 23m 130cd STROBE 960 Lumens / / SOS 150 Lumens

LD22

Max 300 Lumens

■ Max 300 lumens output

Dual output modes (tactical and outdoor)

Four brightness levels

Strobe and SOS function



SIZE: Length: 155mm (6.1 in) Head diameter: 21.5mm (0.8 in)

WEIGHT: 72g (2.5 oz) excluding battery

The Fenix LD22 flashlight features dual modes: outdoor mode and tactical mode activated by 2*AA batteries, delivers 300 lumens maximum output. Ultra compact with 72 grams in weight, and stainless steel side button, make LD22 competent from outdoor lighting to military tactical mission.

ANSI/PLATO FL1												
MODE	MODE OUTPUT TACTICALOUTDOOR RUNTIME DISTANCE INTENSITY IMPACT RESISTANT WAS											
TURBO	300 Lumens	~	√	40min	1h 25min	120m	3600cd					
HIGH	100 Lumens		√	5h 5min	7h 10min	71m	1250cd]				
MED	30 Lumens	~	~	22h 30min	25h 5min	40m	400cd	1	IP68			
LOW	5 Lumens		~	90h	100h	14m	45cd	- 1m	Underwater 2m			
STROBE	300 Lumens	~	√	1	/	/	/]				
sos	100 Lumens		~	/	/	/	/	1				

Tactical tail switch

Exquisite and compact design



SIZE: Length: 94mm (3.7 in) Diameter: 19mm (0.7 in)

WEIGHT: 35g (1.2 oz) excluding battery

The Fenix LD09 is fitted with an intelligent drive circuit for compatibility with one 14500 rechargeable Li-ion battery that delivers 220 lumens output, and features 3 brightness levels plus SOS. The one-handed tail switch compliments the compact body size for convenient operation. As an EDC flashlight it integrates high performance and long standby time to be an indispensable companion, not only for you, but also for your family and friends.

	ANSI/PLATO FL1												
MODE	OUT Alkaline/Ni-MH	PUT 14500	Ni-MH	RUNTIME Alkaline	14500	DISTANCE INTENSITY Alkaline/Ni-MH 14500 Alkaline/Ni-MH 14500				IMPACT RESISTANT	WATERPROOF		
HIGH	130 Lumens	220 Lumens	1h 45min	50min	1h	99m	120m	2450cd	3600cd				
MED	50 Lu	ımens	8h 5min	5h	5h 35min	59	9m	850	Ocd	1m	IP68,		
LOW	3 Lui	3 Lumens 70h 43h 58h 18m 80cd		cd	""	underwater 2m							
sos	50 Lu	ımens	/	/	/		/		1				

Max 100 Lumens

- Exquisite, high intensity flashlight
- Broad beam lens
- 3 brightness levels
- Pushbutton tail switch
- Powered by one AAA battery



SIZE: Length: 76mm (3.0 in) Diameter: 15mm (0.6 in) WEIGHT: 16g (0.6 oz) excluding battery

Small but mighty can describe this LD02 flashlight that offers up to 100 lumens of light with a range of up to 45m, all in a tiny 76mm package that will easily fit in your pocket or on your keychain. Designed to give instant lighting wherever or whenever you need it, the LD02 provides 3 brightness levels to strike a balance between high output and long runtime.

	ANSI/PLATO FL1											
MODE	OUTPUT	RUN Ni-MH	TIME Alkaline	DISTANCE INTENSITY		IMPACT RESISTANT	WATERPROOF					
HIGH	100 Lumens	45min	30min	45m	505cd							
MED	25 Lumens	4h 15min	4h 15min	22m	120cd	1m	IP68, underwater 2m					
LOW	8 Lumens	14h 30min	15h	12m	35cd							

Max 320 Lumens

NEW

- Exquisite, portable design
- Neutral white light, better color rendering

Compatible with 14500 rechargeable Li-ion battery

■ Tactical tail switch plus stainless steel side switch



SIZE: Length:102.5mm(4.0 in) Body diameter:21.5mm(0.9 in) Head diameter:21.5mm(0.9 in)

WEIGHT: 56g (2.0 oz) excluding battery







The redesigned Fenix LD12 is now compatible with 14500 rechargeable Li-ion batteries. It's fitted with a CREE XP-G2 R5 neutral white LED for better color rendering, and delivers maximum 320 lumens. With four brightness levels plus strobe mode, and convenient dual switch, the LD12 is definitely the must-have flashlight for everyday carry.

ANSI/PLATO FL1												
MODE	OUT Alkaline/Ni-MH		Alkaline	RUNTIME Ni-MH	14500	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
TURBO	150 Lumens	320 Lumens	50min	1h 45min	1h	94m/135m	2200cd/ 4500cd					
HIGH	70 Lumens		3h	5h 40min	3h 30min	67m	1100cd		IP68,			
MED	30 Lu	mens	9h 40min	13h	11h	45m	500cd	1m	underwater 2m			
LOW	5 Lumens		40h	60h	50h	18m	80cd		2111			
STROBE	150 Lumens	320 Lumens	/	/	1	1	1					



- Compact and handy
- Max output of 1000 lumens
- Dual switches work separately to avoid accidental operation
- 5 output modes plus strobe and SOS



SIZE: Length: 122mm (4.8 in) Diameter: 24mm (0.95 in)

WEIGHT: 72g (2.5 oz) excluding battery

The handy Fenix E35UE measures only 122mm in length, but delivers a surprisingly powerful 1000 lumens from only one 18650 battery. The light is also compatible with the hardy CR123A batteries. Dual side switches operate separately to give access to the 5 output modes plus strobe and SOS, and a specially designed lockout function avoids inadvertent operation. Industrial design details such as a digitally regulated output and an IPX8 waterproof structure present you with optimal user-friendliness. Without doubt, the E35UE can act as a versatile aid in- as well as outdoors.

ANSI/PLATO FL1 MODE OUTPUT RUNTIME DISTANCE INTENSITY IMPACT RESISTANT WATERPROOF TURBO 1000 Lumens 1h 50min 160m 6400cd HIGH 450 Lumens 106m 2800cd MED 150 Lumens 11h 50min 61m 900cd IP68, LOW 50 Lumens 42h 30min 37m 300cd 1m underwater ECO 8 Lumens 14m 45cd STROBE 1000 Lumens 150 Lumens

E25 Ultimate Edition
Max 1000 Lumens

- Max 1000 lumens
- Compatible with 14500 rechargeable Li-ion batteries
- 5 brightness levels, plus strobe and SOS
- Dual side switches that work independently



SIZE: Length: 161mm (6.3 in) Diameter: 19.6mm (0.8 in) Head diameter: 25.4mm (1.0 in) WEIGHT: 87g (3.1 oz) excluding battery

The E25UE breaks the custom by being Fenix's very first ultra-bright 2 AA flashlight by utilizing an intelligent drive circuit. With a CREE XP-L LED and compatibility with 14500 rechargeable Li-lon batteries, it aims to outshine competitors with its maximum of 1000 lumens, to work better with the 5 general brightness levels plus strobe and SOS, and to last longer (up to 100 hours) on Eco mode. The dual side switches operate independently to allow simplicity of operation, and a specially designed lockout function avoids inadvertent operation. All of these innovative yet practical elements enhance the E25UE as an ideally portable flashlight which combines power, performance and durability.

	ANSI/PLATO FL1											
MODE	Alkaline/Ni-MH 14500		RUNTIME Ni-MH Alkaline 14500		DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
TURBO	3O / 1000 Lume		/	/	50min	200m	10000cd					
HIGH	GH 350 Lumens		1h 30min	50min	2h 15min	112m	3100cd					
MED	160 L	umens	4h 35min	2h 10min	5h 5min	76m	1400cd		IP68,			
LOW	50 Lu	ımens	13h 25min	13h 10min	16h 30min	43m	450cd	1m	underwater			
ECO	5 Lu	mens	100h	90h	95h	13m	40cd		2m			
STROBE	ROBE 350 Lumens 1000 Lumen		/	1	/	1	1					
sos	160 L	umens	/	/	/	1	1					
303	SOS 160 Lumens			/	1	1	/					

Max 265 Lumens

- Max 265 lumens
- Far-reaching 210m beam
- 4 brightness levels
- One-button operation



SIZE: Length: 154mm (6.1 in) Body diameter: 21mm (0.8 in) Head diameter: 25.4mm (1.0 in) WEIGHT: 90g (3.7 oz) excluding batteries

The Fenix E20 features convenience and practicality. With 2 easy-to-get AA batteries, it delivers a maximum output of 265 lumens and a far-reaching throw of 210m. A rear tail switch allows for one-handed operation to choose from the 4 brightness levels. The E20 is believed to be an excellent choice when having to cope with either outdoor or spare home lighting.

	ANSI/PLATO FL1											
MODE	OUTPUT	IMPACT RESISTANT	WATERPROOF									
TURBO	265 Lumens	1h 20min	30min	210m	11000cd							
HIGH	95 Lumens	6h 45min	4h 45min	118m	3450cd		IP68,					
MED	35 Lumens	22h 35min	20h 5min	68m	1150cd	1m	underwater 2m					
LOW	8 Lumens	75h	75h	27m	190cd							

Max 450 Lumens

- Compatible with 16340 Li-ion and CR123A batteries
- 4 brightness levels
- Twisty head switch
- Compact and handy



SIZE: Length: 64.8mm (2.6 in) Diameter: 19mm (0.8 in) Head diameter: 22mm (0.9 in) WEIGHT: 29g (1.1 oz) excluding battery

Due to its size the Fenix E15 is a keychain-sized flashlight. Its high performance will surprise you, as the intelligent drive circuit boosts the output to deliver a maximum output of 450 lumens from only one 16340 Li-ion battery, and also ensures compatibility with CR123A batteries. The twisty head switch regulates the 4 output levels to meet your various lighting demands for daily use, hiking, searching and more.

ANSI/PLATO FL1											
MODE OUTPUT 16340 CR123A		RUN 16340	TIME CR123A	DIST 16340	ANCE CR123A	INTEI 16340	NSITY CR123A	IMPACT RESISTANT	WATERPROOF		
TURBO	450 Lumens	270 Lumens	55 min	1h 35min	132m	91m	4360cd	2050cd			
HIGH		10 nens	3h 15min	5h 5min	58	3m	800	0cd	1m	IP68,	
MED	5 Lum	0 nens	9h 25min	12h 30min	38	3m	350	Ocd	ım	underwater 2m	
LOW	Eum	3 nens	40h	72h	15	5m	55	icd			



SIZE: Length: 90mm (3.5 in) Diameter: 19mm (0.7 in)

WEIGHT: 28.5g (1.0 oz) excluding battery

The E12 is a compact keychain flashlight. Powered by one AA battery, the light blasts out a max 130 lumens, and runs up to 40 hours on Low mode. Activating the light or choosing an ideal output is simple and intuitive – click the tail switch to switch on the light, then tap it for output selection.

	ANSI/PLATO FL1											
MODE	ОИТРИТ	RUN Ni-MH	TIME Alkaline	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
HIGH	130 Lumens	1h 30min	1h	88m	1936cd							
MED	50 Lumens	6h 30min	3h 30min	51m	650cd	1m	IP68, underwater 2m					
LOW	8 Lumens	40h	22h	19m	95cd							

Max 13 Lumens

 Utilizes Nichia white GS LED with a lifespan of 100,000 hours

 Constant current circuit design



SIZE: Length: 71mm (2.8 in) Diameter: 14.2mm (0.6 in) WEIGHT: 14g (0.5 oz) excluding battery

Fenix E01 is a portable mini LED flashlight, featuring a compact body, long runtime and constant brightness, plus the amazing reliability, durability and water resistance that only a Fenix product can supply, this flashlight is greatly loved by the public. The E01 will be a great choice as gift or souvenir, or for EDC.

ANSI/PLATO FL1											
OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF						
13 Lumens	16h 30min	21m	115cd	1m	IP68, underwater 2m						



E05

Max 85 Lumens

- Optimum output-to-weight ratios
- Broad beam lens
- Three brightness levels
- Twist switch
- Powered by one AAA battery





SIZE: Length: 66.5mm (2.6 in) Diameter: 15mm (0.6 in)

WEIGHT: 12.5g (0.4 oz) excluding battery

The Fenix E05 flashlight turns AAA-tiny into useful personal lighting with 85 lumens max output. Simple twist switch operation manages three brightness levels in this 6.6cm flashlight. Durable aircraft-grade aluminum construction and a broad beam lens are ready for action at a moment's notice.

ANSI/PLATO FL1											
MODE	OUTPUT	RUN Ni-MH	TIME Alkaline	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
HIGH	85 Lumens	1h	45min	45m	505cd						
MED	25 Lumens	4h 15min	4h 15min	18m	85cd	1m	IP68, underwater 2m				
LOW	8 Lumens	15h 30min	15h	8m	15cd						



MC SERIES

Angle lights

This Fenix MC series is designed so you can alter the direction of the light beam by adjusting the angle of the light head. The MC series is more versatile than you may need or imagine, be that by hanging it from the attachment hook, hooking it somewhere by using the pocket clip, putting it down somewhere and angling the head to where you need the beam, or even using it as a handheld flashlight, and is perfect for outdoor activities like camping, hiking or mountaineering. It is also perfect for those emergency situations where stronger lights are not necessary, like rescuing or repairs.

MC11

Max 155 Lumens

- Spot-on flexibility
- 90° adjustable head
- 155 lumens burst mode
- 3 brightness levels





SIZE: Length: 99mm (3.9 in) Body diameter: 21.5mm (0.8 in) Head diameter: 25mm (1.0 in)

WEIGHT: 64.8g (2.3 oz) excluding battery














The category-defying MC11 angle light is a favorite amongst trade professionals and recreational users. You can clip it to almost anything, hang it from a lanyard or the built-in D-ring, tail stand it and adjust the light to shine wherever you need it. Powered by one AA battery, the light produces a 155 lumen burst and can run for up to 100 hours on Low mode.

	ANSI/PLATO FL1											
MODE	OUTPUT	RUN Ni-MH	TIME Alkaline	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
BURST	155 Lumens	/	/	75m	1410cd							
HIGH	105 Lumens	2h 15min	1h 40min	65m	1184cd	4	IP68,					
MED	50 Lumens	6h	4h 45min	46m	537cd	1m	underwater 2m					
LOW	3 Lumens	90h	100h	15m	60cd							



FD41

Max 900 Lumens

- Optical lens with total reflective coating
- 360° rotary focusing

■ Cree XP-L HI LED, max 340m throwing distance

Tactical tail switch

Stainless steel side switch



SIZE: Length:146mm(5.8 in)
Body diameter:25.4mm(1.0 in)
Head diameter:40mm (1.6 in)

WEIGHT: 160g (5.6 oz) excluding battery





Fenix FD41 is fitted with an optical lens with total reflective coating. Rotating the focusing ring 360° moves the head and the optical lens forward and backward from the LED, thus regulating the focus between spotlight and floodlight. It delivers max output of 900 lumens and beam distance of 340 meters. The tail switch plus side switch, compatibility with 18650 Li-ion as well as the cold-resistant CR123A, makes the FD41 stand out when searching, camping and photographing outdoors.

	ANSI/PLATO FL1											
MODE	OUTPUT	RUNTIME	DISTA SPOT	ANCE FLOOD	INTEN SPOT	NSITY FLOOD	IMPACT RESISTANT	WATERPROOF				
TURBO	900 Lumens	1h 40min	340m	47m	29000cd	560cd						
HIGH	350 Lumens	3h 50min	218m	30m	12000cd	230cd		IDCO				
MED	150 Lumens	10h 15min	141m	20m	5000cd	100cd	1m	IP68, underwater 2 m				
LOW	10 Lumens	150h	37m	6m	350cd	9cd						
STROBE	900 Lumens	/	/	/	/	/						



FD30

Max 900 Lumens

Dual reflector optical system



SIZE: Length:140.5mm(5.5 in) Body diameter: 23mm (0.9 in) Head Diameter: 25.4mm(1.0 in) WEIGHT: 96g (3.4 oz) excluding battery










Featuring a new style 360° rotary focusing flashlight, Fenix FD30 is fitted with an independently innovative dual reflector optical system. Rotating the focusing ring 360° moves the and the reflector forward and backward from the LED, thus regulating the focus between spotlight and floodlight. It delivers max output of 900 lumens and beam distance of 200 meters. The tail switch plus side switch, compatibility with 18650 Li-ion as well as cold-resistant CR123A batteries, make the FD30 stand out in law enforcement tasks, searching, camping and outdoor photographing.

	ANSI/PLATO FL1											
MODE	OUTPUT	RUNTIME	DISTA SPOT	ANCE FLOOD	INTEI SPOT	NSITY FLOOD	IMPACT RESISTANT	WATERPROOF				
TURBO	900 Lumens	2h	200m	67m	10000cd	1100cd						
HIGH	350 Lumens	4h 30min	117m	43m	3400cd	460cd						
MED	150 Lumens	11h	77m	28m	1500cd	200cd	1m	IP68, underwater				
LOW	50 Lumens	40h 30min	44m	16m	500cd	65cd] ""	2 m				
ECO	8 Lumens	170h	17m	8m	70cd	15cd						
STROBE	900 Lumens	1	/	/	/	/						



Taking advantage of environmental-friendliness and low operating costs, Fenix's rechargeable flashlights can quickly regain power by recharging rechargeable Li-ion batteries, using USB charging from standard AC as well as onboard vehicle charging outlets and personal computers. The charging operation is very simple and convenient. Featuring toughness, reliability and a fully waterproof design, a Fenix rechargeable flashlight is your best choice for military and law enforcement use, hunting, searching and rescuing, etc.



Charging and discharging function


control separately

- Battery level indication
- Detachable shoulder strap











SIZE: Length: 272mm (10.7 in) Body diameter: 52mm (2.1 in) Head Diameter: 108mm (4.6 in) **WEIGHT:** 1234g (43.5 oz) including battery

What amazes all must be RC40, as a rechargeable flashlight features super high output and tough performance, its super high output reaches 6000 lumens and ultra-long distance goes 730 meters. Dual side switches are flexible in controlling five output modes, Strobe and SOS. Tailored rechargeable Li-ion battery pack, plus charging and discharging port with protective circuit, make it super efficient in battery charging, and also enable it supply for other digital devices. Detachable shoulder strap releases hand fatigue, RC40 is invincible companion in searching, rescuing, and self-driving illumination.

		Α	NSI/PLATO FI	_1		
MODE	MODE OUTPUT		DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF
TURBO	6000 Lumens	1h	730m	133200cd		
HIGH	4000 Lumens	1h 50min	633m	100150cd		
MED	2000 Lumens	4h 5min	444m	49250cd		IP68,
LOW	500 Lumens	18h 15min	221m	12200cd	1m	underwater
ECO	45 Lumens	125h	58m	840cd		2m
STROBE	6000 Lumens	1	1	1		
sos	500 Lumens	1	1	1		

RC20

Max 1000 Lumens

- Max 1000 lumens
- Dual mode selection
- Battery level indication
- Dual tail switches



SIZE: Length: 161mm (6.3 in) Body diameter: 25.4mm (1.0 in) Head diameter: 40mm (1.6 in) WEIGHT: 205g (7.2 oz) including battery

The Fenix RC20 flashlight features recharge ability and higher performance, delivering up to 1000 lumens output over a distance of 290m. User-friendly dual tail switches control the 5 output modes and strobe function. With dedicated battery, charger and power detection functions, the RC20 will stand its ground when used for hunting, searching and rescuing, journeying and more.

	ANSI/PLATO FL1											
MODE	OUTPUT	GENERAL MODE	SIMPLIFIED MODE	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
TURBO	1000Lumens	√	√	1h 10min	290m	21100cd						
HIGH	425 Lumens	√		2h 55min	183m	8350cd		IP68, underwater				
MED	150 Lumens	√	√	9h 50min	108m	2900cd	1m					
LOW	10 Lumens	√		120h	29m	200cd		2m				
STROBE	1000Lumens	√	√	/	/	/						

RC09

Max 550 Lumens

- Magnetic charging port for convenient and fast operation
- Innovative dual-purpose charging cable combines magnetic charging & Micro USB
- Compatible with 16340 and CR123A battery
- Reversible body clip and magnetic absorption base



SIZE: Length: 72mm (2.8 in.) Diameter: 21.5mm (0.9 in.) WEIGHT: 45g (1.6 oz) excluding battery

The Fenix RC09 is an all-season rechargeable flashlight, featuring a magnetic suction charging port. The micro USB side of the dual-purpose charging cable allows charging of other digital devices also. Due to the intelligent drive circuit, the flashlight is compatible with low-cost 16340 as well as the cold-resistant CR123A batteries. The compact body plus the reversible body clip make the RC09 not only portable, but also convenient to clip onto a hat when lighting is needed for vehicle maintenance or repairs. The 550 lumens max output support outdoor lovers in confronting outdoor environments.

ANSI/PLATO FL1											
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
TURBO	550 Lumens	35min	115m	3300cd							
HIGH	150 Lumens	2h 35min	60m	900cd	4 ===	IP68, underwater					
MED	50 Lumens	8h 55min	36m	330cd	1m	2m					
LOW	5 Lumens	56h	12m	35cd							

RC11

Max 1000 Lumens

- Magnetic charging port for convenient and fast operation
- Innovative dual-purpose charging cable combines magnetic charging & Micro USB

Max 1000 lumens output





SIZE: Length: 113.5mm(4.5 in) Head diameter: 25.4mm(1.0 in)

WEIGHT: 70g (2.5 oz) excluding battery



The RC11 holds the honor of a conveniently rechargeable flashlight with a magnetic suction charging port. This magnetic charging port along with the innovative dual purpose charging cable which features a magnet and micro USB, make this a smart flashlight, while the cable can also be used as a normal charging cable to charge other digital devices. Compatible with both the 18650 Li-lon and CR123A batteries, the RC11 emits 1000 lumens and has a beam distance of up to 190m.

	ANSI/PLATO FL1									
MODE	OUTPUT	IMPACT RESISTANT	WATERPROOF							
TURBO	1000 Lumens	1h 20min	190m	9050cd						
HIGH	500 Lumens	2h 50min	134m	4500cd						
MED	150 Lumens	11h 10min	72m	1300cd	1m	IP68, underwater				
LOW	50 Lumens	29h 30min	43m	450cd] ""	2m				
ECO	10 Lumens	135h	14m	50cd						
STROBE	1000 Lumens	1	1	/						

RC05

Max 300 Lumens

- Magnetic charging for easy operation
- Innovative charging cable
- Powered by one rechargeable 14500 Li-ion battery
- Two-position body clip and magnetic suction bottom
- One-switch operation, double-click lock function



Charging indicator

SIZE: Length:94mm(3.7 in) Head diameter: 19mm(0.7 in) **WEIGHT:** 36.8g (1.3 oz) excluding battery









As a magnetic charging flashlight the RC05 features an innovative dual-purpose charging cable, integrating magnetic charging and micro USB charging. From only one rechargeable 14500 battery, this EDC puts out a max of 300 lumens, and is compatible with AA batteries as well. A two-way adjustable body clip and a magnetic base make the RC05 rated as ingenious in multiple application scenarios.

ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
TURBO	300 Lumens	55min	90m	2000cd					
HIGH	150 Lumens	2h	60m	990cd]	IP68, underwater			
MED	50 Lumens	6h	37m	340cd	1m				
LOW	5 Lumens	40h	11m	30cd		2m			
STROBE	300 Lumens	1	1	1					

۸G

- Micro USB rechargeable
- Compatible with various batteries
- 960 lumens maximum output
- Optimum output-to-weight ratios
- Tactical tail switch



SIZE: Length: 150mm (5.9 in) Diameter: 25.4mm (1.0 in)

WEIGHT: 99g (3.5 oz) excluding battery

The Fenix UC35 rechargeable flashlight combines high intensity with reliable micro USB charging. A tactical tail switch offers momentary on, and the side switch offers selection of the different output levels. With an optimized beam pattern, the UC35 offers six output levels, including strobe, to cover from daily to outdoor, professional use.

	ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
TURBO	960 Lumens	1h 30min	200m	10000cd						
HIGH	480 Lumens	2h 40min	133m	4400cd	1	IP68,				
MED	180 Lumens	9h 15min	80m	1600cd	1					
LOW	50 Lumens	38h	42m	400cd	- 1m	underwater 2m				
ECO	14 Lumens	150h	18m	80cd						
STROBE	960 Lumens	/	/	1						

Max 960 Lumens

- Ultra compact and high output
- Four brightness levels and strobe mode
- Micro USB charging
- Powered by one 18650 or two CR123A batteries




SIZE: Length: 130mm (5.1 in) Diameter: 25.4mm (1.0 in)

WEIGHT: 77g (2.7 oz) excluding battery

The Fenix UC30 rechargeable flashlight combines high intensity with reliable micro USB charging in a go-anywhere size. Featuring 960 lumens maximum output from a single 18650 battery, the flashlight offers five output levels including strobe to cover from daily to outdoor and professional use.

ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
TURBO	960 Lumens	1h 10min	204m	10404cd					
HIGH	400 Lumens	3h	121m	3650cd		IDEO			
MED	110 Lumens	11h	69m	1150cd	1m	IP68, underwater 2m			
LOW	10 Lumens	120h	18m	80cd	1				
STROBE	960 Lumens	/	/	1					

UCO2SS Max 130 Lumens



- Tiny size with high output
- Micro USB rechargerable
- Reliable twist operation
- Gold and blue colour options

SIZE: Length: 43.2mm(1.7 in) Head diameter: 14mm(0.6 in)

WEIGHT: 18.4g (0.7 oz) excluding battery







NEW





Fenix UC02SS is a USB rechargeable flashlight which has an incredible small body size. From a single 10180 Li-ion battery, it delivers maximum output of 130 lumens. Featuring two output levels, this stainless steel flashlight takes care of your different lighting demands. Exquisite design, IP68 rated structure and easy operation make UC02SS a reliable and helpful lighting tool, and should be your first choice as collector, or as a gift.

ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
HIGH	130 Lumens	25min	48m	570cd	100	IP68,			
LOW	10 Lumens	3h 50min	14m	50cd	1m	underwater 2m			

49

Max 130 Lumens

- Tiny size with high output
- Micro USB rechargerable
- Reliable twist operation
- Three colour options



NEW

SIZE: Length: 43.2mm(1.7 in) Head diameter: 14mm(0.6 in) WEIGHT: 8g (0.3 oz) excluding battery









TINY SIZE WITH HIGH OUTPUT

Only 1.7in. in length, 0.3oz in weight, UCO2 should be your first EDC choice.

Fenix UC02 is a USB rechargeable key chain flashlight which has incredible small body size. From a single 10180 Li-ion battery, it delivers maximum output of 130 lumens. Featuring two output levels, this well-made flashlight takes care of your different lighting demands. Exquisite design, IP68 rated structure and easy operation make UC02 a reliable and helpful lighting tool, and should be your first choice as collector, or as a gift.

ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF			
HIGH	130 Lumens	25min	48m	570cd	1m	IP68,			
LOW	10 Lumens	3h 50min	14m	50cd	1m	underwater 2m			

UC01

Max 45 Lumens

- Fast and secure Micro USB charging
- High performance floodlighting
- Built-in Li-polymer battery and protection circuit
- Battery level indication
- Water resistant to IPX6

SIZE: Length:62mm(2.4 in) width: 22.5mm (0.9 in) Height:10mm (0.4 in)

WEIGHT: 13g (0.5 oz) excluding key chain









You may have murmured with regret: if only I could see a little clearer, or you may have complained about your cellphone battery depleting too fast when you use the phone's built-in flashlight. Do not allow yourself being seized with remorse if an emergency arises! Precaution averts perils, so why not arm yourself with an UC01? This mini light is perfectly suitable for carry-on wearing. The built-in Li-po battery boosts the output wanted during hiking, for reading, etc. The light also features the thoughtful design of a battery level indicator and micro USB charging for more flexible application.

	ANSI/PLATO FL1									
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
HIGH	45 Lumens	1h 20min	7m	12cd						
MED	20 Lumens	3h	5m	6cd	1m	IPX6				
LOW	1 Lumen	50h	1.5m	0.5cd						



Max 1000 Lumens

- 100 meters submersible
- Rotating magnetic ring for one-handed control

Battery level indication



SIZE: Length: 208mm(8.2 in) Body diameter: 26mm(1.0 in) Head diameter: 40mm(1.6 in) WEIGHT: 245g(8.6 oz) excluding battery











Fenix SD20 can be rated as the special design for diving activities. The rotating magnetic ring is easy and convenient for one-handed operation. Maximum 100 meters waterproof ability free you like a fish in underwater exploration and greatly guarantee safety. This diving flashlight also delivers integrated 1000 lumens white light and 105 lumens red light. Bigger button hook and wider lanyard hole maintain SD20 not just outstanding in underwater hunting, but also excellent in lighting and other underwater activities.

	ANSI/PLATO FL1										
M	ODE	OUTPUT	RUNTIME DISTANCE		INTENSITY	IMPACT RESISTANT	WATERPROOF				
WHITE	HIGH	1000 Lumens	3h	172m	7400cd 2900cd						
WHITE	LOW	400 Lumens	7h 30min	108m		1m	underwater 100m				
R	RED	105 Lumens	8h	73m	1300cd						

SD11 Max 1000 Lumens Optical design for photographing Magnetic rotating ring and battery level checking ■ Submersible to 100 meters SIZE: Length :138mm (5.4 in) Body diameter :26mm (1.0 in) Head diameter :34mm (1.3 in) Flashlight clip for photographing WEIGHT: 132.5 g (4.6 oz) excluding battery









Fenix SD11 is designed mainly for underwater photography. "R+" mode is the optimal combination of neutral white light and red light, which is super fit for underwater viewing, photographing and video shooting, since red light is extraordinarily scarce even if you have enough brightness. Featuring neutral white LED and soft wide beam, SD11 is fit for illumination and photography on shore or in water. In addition, 100m waterproof classification makes the flashlight perfect for the demands of deep diving. The magnetic rotating ring offers easy output selection, and safe illumination design warns the user of low battery level. The included flashlight clip and camera mount can be used flexibly and work well with most of the sports cameras and DSLRs.

	ANSI/PLATO FL1										
MODE		OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
WHITE -	HIGH	1000 Lumens	2h	45m	505cd						
	LOW	500 Lumens	3h 40min	30m	225cd	1m	underwater 100m				
R+*		250 Lumens	3h	23m	132cd						

^{*&}quot;R+" is the combination of neutral white light and red light, which is the supplementary lighting for deep-water photographing.





Max 1800 Lumens

- Far-reaching spotlight beam
- Neutral white floodlight, better color redering
- Can be used as a power bank
- Battery level indication

SIZE: Headlamp: Length: 77mm (3.0 in) Width: 52mm (2.0 in) Height: 36mm (1.4 in) Battery case: Length: 116mm (4.6 in) Width: 56mm (2.2 in) Height: 30mm (1.2 in)

WEIGHT: 291g (10.3 oz) excluding batteries

Fenix HP30R is a separated headlamp which is powered by two 18650 Li-ion batteries, where the wrist worn battery case reduces the load bearing of user's head, and maintains optimal performance in cold areas. This headlamp is rechargeable with the Micro USB port in the battery case and can be used as a power bank. Featuring four white spotlight output levels and three neutral white floodlight output levels, the spotlight and floodlight can be switched on simultaneously, delivering a max output of 1800 lumens. HP30R will be the indispensable companion in your mountaineering, searching, skiing and more challenging outdoor activities.

ANSI/PLATO FL1

MODE		OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF
SP	TURBO	1000 Lumens	3h	206m	10689cd		
9	HIGH	400 Lumens	7h 30min	148m	5493cd		
딥	MED	130 Lumens	25h	85m	1800cd		
폭	LOW	30 Lumens	105h	37m	345cd	1m	IP66
Fo	HIGH	800 Lumens	3h	57m	824cd]	
FLOODLIGHT	MED	130 Lumens	20h	35m	311cd		
	LOW	4 Lumens	700h	6m	10cd]	

Ultimate Edition Max 900 Lumens

- Instant 900 lumens burst
- Dual switches control
- Rugged aluminum chassis to shed heat and impact
- Four brightness levels plus SOS mode
- Separate 4*AA battery box
- Excellent fore-aft balance



WEIGHT: 154.2g (5.4 oz) excluding battery

SIZE: LAMP: Length: 67.4mm (2.7 in) Width: 55.9mm (2.2 in) Height: 34.7mm (1.4 in) BATTERY CASE: Length: 88.8mm (3.5 in) Width: 73.7mm (2.9 in) Height: 26.2mm (1.0 in)

Besides an optimized size, Fenix HP15 ultimate edition features a dedicated switch that makes 900 lumens burst mode directly accessible even if the light is off. With six output levels including SOS, rugged aluminum chassis and IPX6 waterproof rating, this headlamp is a reliable tool for mountaineering, searching, caving and more.

ANSI/PLATO FL1									
MODE	OUTPUT	RUN Ni-MH	TIME Alkaline	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF		
BURST	900 Lumens	/	/	178m	7941cd				
HIGH	400 Lumens	3h 30min	3h 10min	119m	3529cd	1	IP66		
MED	150 Lumens	10h	8h	73m	1324cd	1m			
LOW	50 Lumens	40h	44h	42m	441cd] ""	1600		
ECO	10 Lumens	160h	170h	19m	88cd				
sos	50 Lumens	/	/	/	1				

Max 1000 Lumens

NEW

- Long-range spotlight
- Neutral white floodlight
- Micro USB rechargeable battery case
- Battery level indication and low-power reminder



WEIGHT: 183.5g (6.5 oz) excluding battery

SIZE: LAMP: Length: 60mm (2.4 in) Width:54mm (2.1 in) Height: 32.5mm (1.3 in) BATTERY CASE: Length: 82.5mm (3.2 in) Width: 50mm (2.0 in) Height: 35mm (1.4 in)









HP25R defines extreme versatility. It features not only recharging capability, but also the handy combination of neutral white floodlight and far-reaching spotlight. However complex the environment may be, HP25R responds with impressive performance, whether it is in hiking, camping, searching, cave exploration and more. This user-friendly headlamp has a battery level indicator, and a micro USB port for charging when your 18650 battery lets you down.

A A	101	/DI	ATO	
AIN		/PI	$\Delta I U$	

	MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF
골	HIGH	350 Lumens	2.5h	44m	484cd		
8	MED	130 Lumens	9h	25m	158cd	1m	IP66
OODLIGHT	LOW	30 Lumens	40h	13m	46cd		
뽘	ECO	4 Lumens	150h	6m	11cd		
SA	TURBO	1000 Lumens	1.5h	187m	8772cd		
SPOTL	HIGH	350 Lumens	4.5h	109m	3001cd] ''''	
댎	MED	130 Lumens	12h	66m	1108cd		
[폭]	LOW	30 Lumens	42h	34m	296cd		
	RED	0.2 Lumens	96h	1	/		
	FLASH	0.2 Lumens	192h	/	/		

Belt-mounted battery box

USB output for emergency power

■ 450 lumens white light

SIZE: Light: Length: 76mm (3.0 in)
Width: 55.7mm (2.2 in)
Height: 31.5mm (1.2 in)
Battery Case: Length: 116.6mm (4.6 in)
Width: 56.3mm (2.2 in) Height: 29.6mm (1.2 in)

WEIGHT: 280.5g (9.9 oz) excluding battery









USB output for emergency power

Belt-mounted battery box

The Fenix HP40F (for fishing) headlamp features a 450 lumens white light and a powerful blue LED with a 24m beam distance. The belt-mounted battery box removes weight from the head, and provides 8,5 hours of night fishing time. When needed, the USB port of the battery box is ready to recharge any critical or communication devices.

	ANSI/PLATO FL1												
MODE	WHITE LIGHT		BLUE	BLUE LIGHT		WHITE LIGHT		BLUE LIGHT		WATERPROOF			
WIODE	OUTPUT	RUNTIME	OUTPUT	RUNTIME	DISTANCE	INTENSITY	DISTANCE	INTENSITY	RESISTANT	WAILKFROOF			
TURBO	450 Lumens	6h	1	1	110m	3062cd	,	/	1m	IP66			
HIGH	180 Lumens	15h 10min	50 Lumens	8h 30min	70m	1225cd							
MED	65 Lumens	48h	28 Lumens	14h	42m	442cd	_ ′						
LOW	8 Lumens	280h	12 Lumens	32h	15m	54cd							
sos	SOS 180 Lumens			/									



HP12

Max 900 Lumens

IP68 waterproof and dustproof rating
Excellent fore-aft balance
Rugged aluminum housing
900 lumens burst mode
Four brightness levels

WEIGHT: 145g (5.1 oz) excluding battery

SIZE: LAMP: Length: 62.1mm (2.4 in) Width: 41.2mm (1.6 in) Height: 33.3mm (1.3 in) BATTERY CASE: Length: 93.4mm (3.7 in) Width: 41.2mm (1.6 in) Height: 33.3mm (1.3 in)

The powerful waterproof HP12 headlamp features 900 lumens burst mode with a beam distance of 123 meters. The separate battery compartment provides excellent fore-aft balance and supports both rechargeable 18650 Li-ion battery and primary CR123A batteries. Rugged aluminum housing with IP68 waterproof and dustproof rating, HP12 is perfectly fit for technical and dynamic activities.

ANSI/PLATO FL1											
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
BURST	900 Lumens	/	123m	3784cd							
HIGH	400 Lumens	3h 45min	82m	1682cd		IP68 underwater 2m					
MED	150 Lumens	10h 10min	50m	631cd	2m						
LOW	50 Lumens	36h	29m	210cd							
ECO	10 Lumens	145h	13m	42cd							



HL60R Max 950 Lumens

Red light source supplies supplementary lighting

Full-metal housing, waterproof to IPX8 standard

Neutral white light for better color rendering

- Micro USB rechargeable
- Max 950 lumens output






Desert vellow


SIZE: Length: 87mm (3.4 in) Width: 46mm (1.8 in) Height: 51mm (2.0 in) WEIGHT: 121g (4.3 oz) excluding battery











Featuring a Micro USB port for go-anywhere charging, the HL60R Headlamp delivers a maximum output of 950 lumens, beam throw of up to 116 meters and runtime of up to 100 hours from just one 18650 Li-ion battery. This feature-rich headlamp is equipped with neutral white LED for better color rendering, a side switch to activate five output modes and a red light alert mode. The HL60R all-season headlamp is designed with an all-metal housing, and is complete with the ANSI IPX8 waterproof classification.

	ANSI/PLATO FL1											
MODE OUTPUT		RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF						
TURBO	950 Lumens	48min	116m	3396cd								
HIGH	400 Lumens	3h	76m	1430cd	- 1m	IP68, underwater 2m						
MED	150 Lumens	10h	46m	536cd								
LOW	50 Lumens	29h	27m	179cd								
ECO	5 Lumens	100h	8m	18cd								
RED LIGHT	1 Lumen	100h	/	/								

HL55 Max 900 Lumens

900 lumens burst mode

Optimum output-to-weight ratio

Powered by one 18650 battery

All metal housing

■ IP68 protection rating



SIZE: Length: 84mm (3.3 in) Width: 46mm (1.8 in) Height: 48mm (1.9 in)

WEIGHT: 115g (4.1 oz) excluding battery

The Fenix HL55 headlamp offers four useful brightness levels plus a 900 lumens burst mode, and up to 100 hours of runtime from the high-capacity 18650 cell. Neutral white light means superior definition and penetration in high humidity environments. A 116m carry distance reaches further while the head-bound side switch is all you need for On/Off, output selection and instant burst.

ANSI/PLATO FL1 OUTPUT RUNTIME DISTANCE IMPACT RESISTANT WATERPROOF MODE INTENSITY BURST 900 Lumens / 116m 3380cd HIGH 3h 45min 79m 1577cd 420 Lumens IP68, MED 165 Lumens 50m 620cd 1m underwater LOW 29m 207cd 55 Lumens 30h 10 Lumens 38cd

Max 365 Lumens

- Featherlight
- All-weather performance
- Truly versatile



SIZE: Length: 63.8mm (2.5 in) Width: 32mm (1.3 in) Height: 30mm (1.2 in) WEIGHT: 57g (2 oz) excluding battery

Ultra compact design and powered by CR123A battery, the 2-meter submersible all-weather HL50 headlamp helps you reach new heights in your outdoor adventures. The Fenix HL50 headlamp features 365 lumens neutral white output and the ability to use either CR123A or AA batteries. You can also pop the lighting head out for handheld or keychain use with the always-ready HL50.

ANSI/PLATO FL1											
MODE	OUT CR123A	PUT Ni-MH AA	RUN CR123A	TIME Ni-MH AA	DISTA CR123A	ANCE Ni-MH AA	INTEN CR123A	NSITY Ni-MH AA	IMPACT RESISTANT	WATERPROOF	
BURST	365 Lumens	285 Lumens	/	/	77m	68m	1480cd	1156cd	- 1m	IP68, underwater 2m	
HIGH	170 Lumens	150 Lumens	3h	2h	53m	49m	689cd	608cd			
MED	60 Lumens	55 Lumens	9h 45min	6h 20min	31m	30m	243cd	223cd			
LOW	4 Lumens	3 Lumens	150h	110h	8m	7m	16cd	12cd			

- Additional red light
- Three brightness levels plus SOS mode
- Unique broad beam system

WEIGHT: 86.6g (3.1 oz) excluding battery





SIZE: Length: 70mm (2.8 in) Width: 47.5mm (1.9 in) Height: 37.5mm (1.5 in)

Powered by 2 AA batteries, HL30 delivers a 230 lumens output and runs for 160 hours on low mode. Featuring the unique broad beam system, HL30 illuminates the entire scene with unmatched clarity and consistency in camp, hobby or work situations. The integrated red light protects night vision while making map reading easier even under adverse conditions. HL30 headlamp is a great choice for camping, hiking and more.

ANSI/PLATO FL1 MODE DISTANCE INTENSITY IMPACT RESISTANT WATERPROOF OUTPUT HIGH 140 Lumens 3h 30min 40m 405cd MED 50 Lumens 12h 14h 24m 145cd LOW 4 Lumens 150h 160h 7m 12cd BURST 230 Lumens 2h 25min 2h 51m 665cd IP66 sos 50 Lumens RED CONSTANT-ON 1 Lumen LIGHT FLASH 1 Lumen

Max 150 Lumens

- IP68 rated structure
- Rugged aluminum housing
- Three brightness levels
- Powered by one AA battery







SIZE: Length: 71mm (2.8 in) Width: 38.9mm (1.5 in) Height: 40mm (1.6 in)

WEIGHT: 52g (1.8 oz) excluding battery

Rugged Aluminum housing and waterproof construction, the IP68 rated HL23 headlamp is ready for anything you can throw at it. Equipped with a powerful Cree XP-G2 LED, this single AA battery powered headlamp provides 150 lumens output with 55 meters beam distance. Featuring three brightness levels, HL23 is a great choice for your nighttime adventures.

ANSI/PLATO FL1											
MODE	OUTPUT	RUN Ni-MH	TIME Alkaline	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
HIGH	150 Lumens	1h 20min	1h	55m	758cd	1.5m	IP68, underwater 2m				
MED	50 Lumens	5h 40min	4h 25min	32m	253cd						
LOW	3 Lumens	100h	110h	8m	15cd						

HL26R

Max 500 Lumens

NEW


- Multiple outputs with impressive runtime
- Spotlight and floodlight for options
- Built-in rechargeable Lipolymer battery
- Dedicated headband for sports
- Power level indication



SIZE: Length: 65mm (2.6 in) Width: 44mm (1.7 in) Height: 37mm (1.5 in) WEIGHT: 86g (3.0 oz) including batteries











Fenix HL26R is an integrated, trail running headlamp. With built-in rechargeable Li-polymer battery, it can be charged through Micro USB port. Featuring four spotlight brightness levels, three floodlight modes, dual switches for fast operation, plus IP66 dustproof and waterproof classification, HL26R is the best choice for trial running, hiking etc.

	ANSI/PLATOFL1											
ı	MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
SP SP	TURBO	500 Lumens	1h 30min	100m	2564cd							
SPOTLIGHT	HIGH	130 Lumens	6h 30min	57m	810cd							
	MED	70 Lumens	13h	42m	450cd							
폭	LOW	30 Lumens	17h	30m	225cd	1m	IP66					
F	HIGH	40 Lumens	16h	10m	24cd							
FLOODLIGH	LOW	4 Lumens	150h	4m	4cd							
9 유	SOS	40 Lumens	32h	/	/							

■ Reflective, sweat-block headband



67







NEW


SIZE: Length: 63mm (2.5 in) Width: 41.5mm (1.6 in) Height: 35mm (1.4 in)

WEIGHT: 60g (2.1 oz) excluding batteries

The Fenix HL15 is a lightweight running headlamp. It is equipped with a reflective headband, one neutral white LED for better color rendering, and two red LEDs to alert others. Featuring four brightness levels plus IP67 waterproof classification, the HL15 is perfect for road running, hiking, camping etc.

ANSI/PLATO FL1											
MODE	OUTPUT	RUN Ni-MH	TIME Alkaline	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF				
TURBO	200 Lumens	1h 10min	1h 30min	50m	500cd	1m	IP67				
HIGH	70 Lumens	3h 30min	4h	29m	208cd						
MED	30 Lumens	8h 30min	12h 30min	18m	82cd						
LOW	4 Lumens	37h	58h	8m	18cd						
ECO	0.2 Lumens	75h	85h	1	1						
FLASH	0.2 Lumens	150h	170h	1	1						

Max 70 Lumens





The Fenix HL10 headlamp is both reliable and versatile in functionality. Powered by one AAA battery, this extremely lightweight headlamp delivers a maximum output of 70 lumens. The HL10 can be used as a traditional headlamp, or the detachable light can serve as a freestanding or handheld mini flashlight. Its rotating lens allows it to adjust from spotlight to floodlight. From running to night reading, the HL10 is adaptable to multiple lighting needs.

	ANSI/PLATO FL1											
MODE	ОИТРИТ	RUN Ni-MH	TIME Alkaline	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF					
HIGH	70 Lumens	1h	40min	30m	229cd	1m	IP68, underwater 2m					
MED	30 Lumens	3h10min	2h 30min	19m	92cd							
LOW	4 Lumens	26h	24h	6m	10cd							

Max 8 Lumens



- Compact but multi-functional; various ways of
- Ultra long run- and standby time
- Dual lighting mode (white and red)
- Tailored nylon bag



SIZE: Length: 36mm (1.4 in) Width: 38mm (1.5 in)

WEIGHT: 13g (0.5 oz) excluding battery

Height: 18mm (0.7 in)





The Fenix HL05 provides multi-functionality belied by its small body size. Measuring only 13g in weight the HL05 features 4 output modes, including red flashing, and delivers up to 280 hours of illumination added to an ultra-long standby time. This versatile lighting source can be worn on the head, or clipped on to a backpack or hat, and is the best-buy supplementary lighting source for hiking, reading, alerting and red illumination.

	ANSI/PLATO FL1											
MODE	OUTPUT	RUNTIME	DISTANCE	INTENSITY	IMPACT RESISTANT	WATERPROOF						
HIGH	8 Lumens	50h	4.5m	5.3cd		IP68,						
LOW	3 Lumens	90h	2.8m	2.0cd	4							
RED	0.2 Lumens	75h	1	1	1m	underwater 2m						
RED FLASH	0.2 Lumens	280h	1	1								



REGIR Max 1600 Lumens

- OLED digital display
- Back-lit plus/minus switch
- Quality neutral white LEDs
- Dual distance beam system
- USB rechargeable
- Water-resistant and full-metal



Best New Gear Awa



Best in Show Awar



ISPO Award Asia Products Gold Winner 2015/2016



INDUSTRY AWARD 201







SIZE: Length: 114mm (4.5 in) Width: 50.4mm (2.0 in) Height: 32mm (1.3 in)

WEIGHT: 220g (7.8 oz) including battery

The BC30R is the first Fenix light fitted with an OLED display panel, which displays the remaining runtime at the current output level, and the battery percentage clearly, as riders need not only comfortable lighting, but also need to know the remaining runtime, whether during mountain biking or urban riding. The BC30R USB rechargeable bicycle light features the industry's first digital display screen for confidence-inspiring readings. A compact body with built-in rechargeable batteries and quick-release fitment allow this versatile light to light your trails with outputs up to 1600 lm, and runtimes reaching over 20 hours.

ANSI/PLATO FL1								
MODE	OUTPUT	RUNTIME	DISTANCE	IMPACT RESISTANT	WATERPROOF			
BURST	1600 Lumens	/	155m					
HIGH	800 Lumens	2h 35min	115m					
MED	500 Lumens	4h 30min	88m] 1m	IP66			
LOW	200 Lumens	11h 50min	57m		IFOO			
ECO	100 Lumens	20h 20min	41m					
FLASHING	200 Lumens	/	1					



BC30

Max 1800 Lumens

- Dual Distance Beam System
- 1800 lumens burst mode
- Full aluminum housing
- Quick-release mounting system



SIZE: Length: 126.7mm (5.0 in) Width: 50mm (2.0 in) Height: 31.8mm (1.3 in)

WEIGHT: 161g (5.7 oz) excluding battery

The Fenix BC30 bicycle light puts self-contained 1800 lumens max output at the ready. Remote burst activation and Fenix's exclusive Dual Distance Beam System make the BC30 beam effective on road or trail up to 170m distance. Choose between the 18650 rechargeable or CR123A batteries to power the four brightness levels and warning mode, all guarded by a rugged bar-mounted housing.

	ANSI/PLATO FL1									
M	ODE	OUTPUT	RUNTIME	DISTANCE	IMPACT RESISTANT	WATERPROOF				
В	URST	1800 Lumens	1	170m						
Н	HIGH	1200 Lumens	1h 50min	135m						
N	MED	500 Lumens	5h	87m	1m	IDee				
L	_OW	200 Lumens	11h	56m	""	IP66				
Е	ECO	100 Lumens	20h	41m						
FLA	SHING	200 Lumens	1	1						

RT30R Max 1800 Lumens

Dual Distance Beam System

■ 1800 lumens neutral white output

Instant burst with remote pressure switch

- Rechargeable battery pack
- Compact aluminum housing



SIZE: Light: Length: 74mm (2.9 in) Width: 50.6mm (1.99 in) Height: 43.5mm (1.7 in) Battery Case: Length: 87mm (3.4 in) Width: 59mm (2.3 in) Height: 37mm (1.5 in)

WEIGHT: 154g (5.4 oz) excluding battery pack



BT30R rechargeable bike light is what you bring to a mountain bike descent. The light features 1800 lumens output with remote burst activation and the exclusive Dual Distance Beam System to help you see further and go faster.

ANSI/PLATO FL1								
MODE	OUTPUT	RUNTIME	DISTANCE	IMPACT RESISTANT	WATERPROOF			
BURST	1800 Lumens	/	170m					
TURBO	1200 Lumens	1h 50min	135m					
HIGH	500 Lumens	5h 15min	83m	1m	IP66			
MED	200 Lumens	12h 50min	57m] ""	1200			
LOW	100 Lumens	22h 35min	40m					
FLASHING	200 Lumens	1	1					



BC21R Max 880 Lumens

WEIGHT: 67g (2.4 oz) excluding battery



The Fenix BC21R, an integrated yet versatile rechargeable bicycle light, delivers a max of 880 lumens neutral white light. The four output levels plus flash enrich your cycling activities, and integrated red side lights ensure riding safety. Mounting and dismounting of the light is made easier due to a quick-release handlebar mount. The ability to charge the battery puts the rider in charge of the battery runtime, and prolongs battery life. This well-designed bicycle light can take you anywhere for any activity. It is committed to diversify your bicycling lifestyle and enhance your every ride, be it road racing, casual riding or urban commuting.

ANSI/PLATO FL1								
MODE	OUTPUT	RUNTIME	DISTANCE	IMPACT RESISTANT	WATERPROOF			
TURBO	880 Lumens	1h 20min	125m					
HIGH	380 Lumens	4h 30min	86m					
MED	200 Lumens	8h 30min	62m	1m	IP66			
LOW	100 Lumens	15h 50min	44m					
FLASH	380 Lumens & 100 Lumens	/	1					



Max 650 Lumens

Max 650 lumens output for wide area illumination

- Micro USB for charging and discharging
- Cold-resistant structure
- Separate circuit design



SIZE: Length: 93mm (3.7 in) Width: 93mm (3.7 in) Height: 136mm (5.3 in)

WEIGHT: 412g (14.5 oz) excluding battery









The Fenix CL30R camping lantern features micro USB charging and discharging, neutral white LED's, delivering up to 650 lumens max output and an illumination diameter of up to 35m from either one, two or three 18650 batteries, and six output levels which include eco, turbo and flashing modes. Added to that, combining Fenix's unique cold resistant battery compartment with a charging and battery level indicator, make this camping lantern superb! With an adaptable built-in hanging loop and tripod socket, this is a professional "safeguard" to arm your outdoor campsite environment.

MODE	OUTPUT	RUN 2600mAh	TIME 3500mAh	BEAM DIAMETER	IMPACT RESISTANT	WATERPROOF
TURBO	650 Lumens	4h 30min	6h			
HIGH	350 Lumens	9h	12h			
MED	100 Lumens	38h	51h	35m (Max)		IDC7
LOW	50 Lumens	70h	93h	Solii (iviax)	1m	IP67
ECO	10 Lumens	300h	400h			
FLASHING	100 Lumens	70h	93h			

CL25R

Max 350 Lumens

- High intensity and wide illumination range
- Micro-USB charging function
- Cold-resistant structure
- Neutral white light and red light
- Hanging loop, tripod socket and magnetic base



ISPO (Asia)

Award Gold Winner





Olive green









SIZE: Length: 52mm (2.0 in) Width: 52mm (2.0 in) Height: 99mm (3.9 in) WEIGHT: 130g (4.6 oz) excluding battery and other accessories

Measuring at only 99mm in height and weighing only 130g, this all-season camping lantern lights up an area with a diameter of up to 25m with its 350 lumens max output, and it also features a reliable micro USB charging function and cold-resistant structure. The CL25R offers 6 output modes (including Turbo), red light and a moonlight mode which will deliver illumination for up to 600 hrs. This adaptable lighting source can be hung from its lanyard, attached to metal areas with its built-in magnetic base, or mounted on a tripod.

MODE	OUTPUT	RUN 18650	TIME CR123A	BEAM DIAMETER	IMPACT RESISTANT	WATERPROOF
TURBO	350 Lumens	2h 15min	2h 5min			
HIGH	200 Lumens	5h	4h 10min		4.5	IP66
MED	50 Lumens	23h 45min	18h 50min	25m (Max)		
LOW (MOONLIGHT)	0.8 Lumens	600h	500h	Zom (Max)	1.5m	1200
CONSTANT-ON RED	1.5 Lumens	44h	42h			
FLASHING RED	1.5 Lumens	/	1			



Max 165 Lumens

- All-season performance
- Innovative battery compartment
- Multifaceted globe for maximum output and anti-glare lighting
- Neutral white output plus red light
- Built-in hanging loop and magnet for easy attachment



SIZE: Length: 78.4mm (3.1 in) Width: 45.2mm (1.8 in) Height: 59.1mm (2.3 in)

WEIGHT: 103.2g (3.6 oz) excluding battery

Designed with all-season campers in mind, the CL20 camping lantern supports AA battery and CR123A lithium battery to ensure optimum performance in cold seasons. The premium neutral white LEDs along with exclusive multifaceted globe provide 165-lumen anti-glare light for gear organization and other nighttime camping tasks. With built-in hanging loop and magnet for easy attachment, the additional red light equipped CL20 is a versatile companion whether on campsite or in tent.

MODE	OUTPUT	Ni-MH Battery	RUNTIME Alkaline Battery	CR123A	BEAM DIAMETER	IMPACT RESISTANT	WATERPROOF
TURBO	165 Lumens	2h 23min	3h 10min	2h			
HIGH	100 Lumens	5h 15min	4h 9min	3h 31min		1.5m	IP66
MED	50 Lumens	11h 28min	9h 4min	7h 32min	10m (Max)		
LOW	8 Lumens	71h 40min	56h 40min	46h 50min	Totti (Max)		
RED LIGHT	1.5 Lumens	27h 10min	24h 15min	20h			
sos	1.5 Lumens	1	/	1			

CLO5 LipLight Max 8 Lumens

- Tri-colored LED, seven output modes
- One AAA battery is also durable
- Simple but with reliable operation
- Waterproof to IPX8 standard



SIZE: Length: 72.5mm (2.9 in) Diameter: 18mm (0.7 in)

WEIGHT: 12.8 g (0.5 oz) excluding battery

The Fenix CL05 LipLight, is an EDC emergency light with a tri-colored LED, giving you 7 output modes. It provides you with up to 40 hrs of soft lighting to avoid stumbling in the dark, or can be used as a flashing eye-catching beacon the whole night through.

Furthermore, Fenix designs the CL05 without standby current drain to break the so-called "standby time" limit, and the light is IPX8 waterproofed, which makes the CL05 a true EDC

light, even when having to struggle through the rain. All it needs is an AAA battery.

MODE	OUTPUT	RUN Ni-MH	TIME Alkaline	BEAM DIAMETER	IMPACT RESISTANT	WATERPROOF
HIGH	8 Lumens	3h 20min	4h			
MOONLIGHT	0.8 Lumens	33h	40h			
RED	2 Lumens	8h 30min	11h			IP68,
RED FLASH	2 Lumens	17h	22h	3.4m (Max)	1m	underwater
GREEN	5 Lumens	8h	10h 30min			2m
GREEN FLASH	5 Lumens	16h	21h			
sos	8 Lumens	/	/			





Filter Adapter (AOF-S/S +/M/L)

This is a Fenix flashlight accessory with outstanding filtering ability to maintain strong red/blue/green light which can be used when signaling.

- Uses a toughened ultra-clear glass lens with anti-reflective coating that provides heat resistance and maximum light penetrability
- Anti-roll design, easy to attach, easy to remove



Traffic Wand (AOT-S / M / L)

Fenix traffic wand can convert your flashlight into a glowing orange highvisibility wand. It's the best option for emergency situations and traffic control.





Rechargeable batteries

A protective circuit is built into the anode and covered with a riveted steel hat. The battery is fully covered with the steel shell, thus eliminating the potential risk of short circuiting caused by collision or impact.

- Prevent short circuit
- Multiple protection
- 500 charge cycles

MODEL	TYPE	CAPACITY	VOLTAGE
ARB-L4-4800	26650	4800 mAh	3.7V
ARB-L18-3500	18650	3500 mAh	3.6V
ARB-L18-3400	18650	3400 mAh	3.6V
ARB-L18-2900	18650	2900 mAh	3.6V
ARB-L18-2600	18650	2600 mAh	3.6V
ARB-L16-700	16340	700 mAh	3.6V
ARB-L14-800	14500	800 mAh	3.6V
ARB-L18-3500U	18650+USB	3500 mAh	3.6V
ARB-L18-2600U	18650+USB	2600 mAh	3.6V
ARB-L16-700U	16340+USB	700 mAh	3.6V
ARB-L14-1600U	14500+USB	1600 mAh	1.5V



Remote Pressure Switch (AER-01)

The Fenix remote pressure switch is specifically designed for tactical flashlights, with a pressure sensor for easy and reliable activation. The flashlight is switched on by applying light finger pressure to the switch, and switched off by removing the pressure of the finger. The 80cm cable (max length) allows for remotely controlling the light, making it more agile and convenient for tactical applications, and for hunting.

- Durable for over 100,000 activations. Flashlight is activated by pressing any one of the four sensors.
- Cable made from resilient PU material; coiled length 23cm, expanded length 80cm
- The tail cap is made from T6-grade aluminum with Type III hard-anodized finish for durability and
- Side switch on the tail cap is capable of transmitting current of 1A for a long period of time, and is independent from the pressure pad switch
- Waterproof to IPX8 standard
- The tail cap is 25.4mm in diameter, 40mm in length.
- Pressure pad switch, cable and the tail cap weigh 53.2 grams total



Tactical Remote Pressure Switch (AER-02)

The Fenix AER-02 is made specifically for tactical flashlights. The dual tail switch allows fast and convenient operation in switching on/off, or locking out of the flashlight. The innovative noiseless(no click) design of the switch, with attached Velcro makes this convenient for tactical missions or hunting.

- Noiseless (no click) pressure pad switch (30mm long)with a lifespan of 100000 activations; capable of transmitting current of 3A for a long period of time
- Tactical tail switch capable of constant-on function, and can transmit 3A current for a long period of time
- Velcro design for fast and convenient operation.
- Cable made from resilient PU material can be extended from 24cm to 80cm.
- Tail adapter is made from T6-grade aluminum, type III hard-anodized anti-abrasive finish.
- Waterproof to IPX8 standard
- Tail adapter size: Diameter: 25.4mm (1.0 in) Length: 31.5mm (1.2 in)
- Work with Fenix TK15UE,TK09,PD35TAC,PD35,PD32,UC35 flashlights
- Including pressure pad switch, coiled cable and tail adapter
- Total weight: 65g



Tactical Remote Pressure Switch (AER-03)

Featuring momentary on, constant on and output selection (functions may vary between flashlights), the Fenix AER-03 is dedicated for tactical flashlights. Noiseless (no click)design, with attached Velcro makes it convenient for tactical missions or hunting.

- Work with Fenix TK32, TK16, TK20R(only for ON/OFF operation) flashlights
- Noiseless (no click) pressure pad switch (30mm long)with a lifespan of 100,000 activations, featuring output selection and capable of transmitting current of 3A for a long period of time
- Tactical tail switch capable of constant-on/momentary-on function, and can transmit 3A current for a long period of time
- Velcro design for fast and convenient operation
- Cable made from resilient PU material can be extended from 24cm to 80cm
- Tail adapter is made from T6-grade aluminum, type hard-anodized anti-abrasive finish
- Including pressure pad switch, coiled cable and tail adapter
 Waterproof to IPX8 standard
- Tail adapter size: Diameter: 25.4mm (1.0 in) Length: 31.5mm (1.2 in)
- Total weight: 65 grams (2.3 oz)



Diffuser Tip (AOD-S / M / L)

Diffuser tips can soften the light and work as a camping light, signal light, reading light, tent light, etc.

■ Durable, impact resistant and fireproof to V2 Standard



Rail Mount (ALG-01)

- Adjustable diameter design allows use with a wide range of flashlights
- Universal slide-in flashlight ring
- With plastic spacer flashlights with diameter 23.6 mm-24.2 mm can be fitted
- Without plastic spacer flashlights with diameter 25.4 mm-26.0 mm can be fitted

NEW



Rail Mount (ALG-00)

ALG-00 features the quick detachable Picatinny rail design which suits for tactical firearms with fish oil Picatinny rails. The compatible flashlight diameter ranges from 22.5-26mm, and wrench is needed when clip flashlights. Full-metal housing made of durable aircraft-grade aluminum, and premium type ${\rm III}$ hard-anodized anti-abrasive finish in all black treatment without light reflection.



Quick-release Bike Mount (ALB-10)

Utilizing a unique split-type design for quick release of flashlights, the Fenix ALB-10 bicycle mount can effectively reduce the amount of steps and the time needed for mounting. Featuring Fenix's solidity and compatibility with a wide range of flashlights, this mount will ensure your safety during your night riding.

- Split-type design for quick release
- Fits flashlights with diameter of 18mm—26mm
- Rotating 30 degree design adjusts to any locking angle
- High-quality rubber mat provides shock-resistant and slip-resistant grip without scratching the handlebar
- Anti-aging, solid and able to withstand extended exposure to sunlight and rain



Car Adapter (ARW-10)

Compatible with ARE-C2, ARE-C1, ARE-C2+, ARE-C1+



TK75 Extended Runtime Kit (AET-TK75)

The runtime of the TK75 can be extended with the addition of body tube segments and battery holders. Each segment added extends the runtime equal to the runtime of one TK75.

- Install the kit facing the right direction
- Runtime equal to the runtime of one TK75 is gained with the addition of each extended runtime kit
- The use of more than three kits in one TK75 flashlight is not recommended



AFH-01 Portable Flashlight Tool Case

- Compatible with many Fenix products
- Double layer design expands storage capacity
- Liner made of environmentally friendly EVA
- Material features cushioning, impact resistance, thermal insulation and moisture resistance
- Case is made from PP environmental material
- External size: 280×220×80mm (11×8.7×3.1 in)
- Weight: 594 grams (20.9 oz) case only





Helmet Attachment Hook Kit (ALD-02)

The ALD-02 helmet attachment hook kit includes four plastic hooks and one headband with two silicone gel strips. The anti-slip headband fits well on the helmet, and the hooks keep the headband secure, preventing the headlamp sliding from the helmet. (Not for fully protective outdoor sports headlamps and headlamps with foam lining)

- Four plastic hooks
- Two silicone gel stripes

NEW



Headlamp Attachment (ALG-03)

ALG-03 headlamp attachment is specially designed for HL60R fixation to outdoor or industrial work helmets. It enables fast and convenient attachment and detachment of headlamp to and from helmet, and allows adjustment of the lighting angle of HL60R. It only adds 3mm to product thickness. In addition, it uses thickened blown-sponge, to fit to more helmets in various ways. The glue attaches perfectly to the plastic and will not damage the helmet or the headlamp.


- Fast and convenient for HL60R attachment and detachment to and from helmet
- Make the HL60R lighting angle adjustable
- The used glue will not damage the helmet or the headlamp



Four Channels Smart Charger (ARE-C2⁺)

Fenix ARE-C2+ is a four channels smart charger, which is compatible with different types of Li-ion and Ni-MH/Ni-Cd batteries. High definition LCD screen displays charging status and battery level clearly. In addition, a car charging mode offers high convenience for users.

- LCD display screen for charging and battery level
- Compatible with different types of Li-ion and Ni-MH / Ni-Cd batteries
- AC and DC charging modes
- Input: AC100-240V/50-60Hz/0.35A (max) or DC12-24V/1A (max)
 Output: Li-ion battery 4.2V, 1.0A, Ni-MH / Ni-Cd battery 1.5V, 1.0A
- Rated output power: 6W (Ni-MH/ Ni-Cd), 16.8W (Li-ion)
- Built-in short circuit protection, over current protection, over voltage protection and reverse polarity protection.





Dual Channel Smart Charger (ARE-C1⁺)

Fenix ARE-C1+ is a dual channel smart charger, which is compatible with different types of Li-ion and Ni-MH/Ni-Cd batteries. High definition LCD screen displays charging status and battery level clearly. In addition, a car charging mode offers high convenience for users.

- LCD display screen for charging and battery level
 Compatible with different types of Li-ion and Ni-MH / Ni-Cd batteries
- Input: AC100-240V/50-60Hz/0.35A (max) or DC12-24V/1A (max)
- Output: Li-ion battery 4.2V, 1.0A, Ni-MH / Ni-Cd battery 1.5V, 1.0A
 Rated output power: 3W (Ni-MH/ Ni-Cd), 8.4W (Li-ion)
- Built-in short-circuit protection, over-current protection, over-voltage protection and reverse polarity protection



Dual Channel Smart Charger (ARE-X2)

The Fenix ARE-X2 dual channel smart charger chooses the correct charging current for each battery inserted, for any battery between the 26650 and 10440. It also features micro USB charging and discharging, and LED charging/discharging indicators clearly inform you of the charging status.

- Compatible types of batteries
- Able to charge identical or different batteries sizes simultaneously
- Micro USB charging/USB discharging
- Be able to charge same kind or different kinds of batteries simultaneously
- Micro USB battery charging, USB battery discharging
- Chooses corresponding charging mode depending on each type of battery
- Built-in circuit protects batteries against overcharging, over-discharging, short circuiting and improper battery insertion
- LED charging/discharging indicators



Single Channel Smart Charger (ARE-X1⁺)

Fenix ARE-X1+, the single channel smart battery charger, is built for different sizes of rechargeable Li-ion batteries, as well as Ni-MH and Ni-Cd batteries. In addition, the Micro USB charging port offers versatile universality. While charging, the user-friendly LCD screen indicates the battery level and charging status clearly. Built-in multi-protection guarantees charging safety.

- Compatible with different battery types
- Micro USB charging port
- LCD screen for displaying battery level and charging status
- Multi-protection circuits




Single Channel Smart Charger (ARE-X1)

The Fenix ARE-X1 is a single channel smart charger designed for 18650 and 26650 batteries, and provides charging, discharging and battery power

- Compatible with one 18650 or one 26650 rechargeable Li-ion battery
- Supports micro USB charging and USB discharging
- LED charging/discharging indicator
- LED battery power detection
- Microcomputer chip controlled, digitally regulated charging to extend battery lifetime
- Short circuit, overcurrent, overvoltage and reverse polarity protection

ACCESSORIES COMPATIBILITY GUIDE



NOTE:
* Only for ON/OFF operation.
** Press down the anode side when taking out the battery in case the battery's anode stuck in the battery holder.

FENIX PRODUCTS SPECIFICATION CHART

Model	LED	Max output	Max runtime	Brightness level	IP rating	Dimension	Weight	Battery	Model
TK-SERIES	One MALOLIO	4000 luna ana	0701	4 output levels	IDCO	185×52.5×87.5mm	575a	4*40050	TK-SERIES
TK75 TK65R	Cree XM-L2 U2 Cree XHP70	4000 lumens 3200 lumens	270h 125h	5 output levels	IP68 IP68	185×52.5×87.5mm 270×61.5×36.5mm	575g 396g	4*18650 5000mAh/7.2v rechargeable battery pack included	TK75 TK65R
TK47	Cree XHP35 HI	1300 lumens	220h	6 output levels	IP68	266.2×61.5×28.6mm	376g	2*18650	TK47
TK47UE	Cree XHP70	3200 lumens	170h	7 output levels	IP68	266.2×61.5×28.6mm	365g	2*18650	TK47UE
TK35	Cree XM-L2 U2	960 lumens	240h	5 output levels	IP68	159×43×48mm	217g	4*CR123A/2*18650	TK35
TK35UE	Cree XHP 50	2000 lumens	160h	5 output levels	IP68	161×50mm	240g	4*CR123A/2*18650	TK35UE
TK32 2016	Cree XP-L HI V3	1000 lumens	170h	8 output levels	IP68	159x25x52mm	175g	2*CR123A/1*18650	TK32 2016
TK20R TK16	Cree XP-L HI V3 Cree XM-L2 U2	1000 lumens 1000 lumens	160h	4 output levels 4 output levels	IP68 IP68	151.5×25×34mm 140×25×34mm	141g 122g	1*18650 2*CR123A/1*18650	TK20R TK16
TK15UE	Cree XPL HI V3	1000 lumens	150h 135h	4 output levels	IP68	140^25^34fffff 142.5x 25.4x34mm	141g	2*CR123A/1*18650	TK15UE
TK09	Cree XP-L HI	900 lumens	37h	3 output levels	IP68	130×25.4×34mm	105g	2*CR123A/1*18650	TK09
PD-SERIES									PD-SERIES
PD40R	Cree XHP70	3000 lumens	55h	5 output levels	IP68	138.5×34×30mm	126g	26650 rechargeable power battery included	PD40R
PD35 TAC	Cree XP-L V5	1000 lumens	140h	5 output levels	IP68	137×25.4mm	89g	2*CR123A/1*18650	PD35 TAC
PD35	Cree XM-L2 U2	960 lumens	150h	5 output levels	IP68	139×25.4mm	87g	2*CR123A/1*18650	PD35
PD32 2016 PD25	Cree XP-L HI Cree XP-L V5	900 lumens 550 lumens	240h 100h	5 output levels 4 output levels	IP68 IP68	129.5×22.6×24mm 93×21.5mm	77g 47g	2*CR123A/1*18650 2*CR123A/1*18650	PD32 2016 PD25
LD-SERIES	Cree XP-L V5	550 lumens	Toon	4 Output levels	IP66	93*21.50000	479	2 CR123A/1 18050	LD-SERIES
LD75C	Cree XM-L2 U2 & XM-L color	4200 lumens	175h	9 output levels	IP68	158×52×74mm	430g	4*18650/8*CR123A	LD75C
LD41	Cree XM-L2 U2	960 lumens	200h	4 output levels	IP68	175×40mm	190g	4*AA	LD41
LD22	Cree XP-G2 R5	300 lumens	100h	4 output levels	IP68	155×215mm	72g	2*AA	LD22
LD12 2017	Cree XP-G2 R5(Neutral white)	320 lumens	60h	4 output levels	IP68	102.5×21.5×20.5mm	56g	1*14500/1*AA	LD12 2017
LD09	Cree XP-E2 R3	220 lumens	58h	3 output levels	IP68	94×19mm	35g	1*14500/1*AA	LD09
LD02 E-SERIES	Cree XP-E2	100 lumens	15h	3 output levels	IP68	76×15mm	16g	1*AAA	LD02 E-SERIES
E-SERIES E35UE	Cree XM-L2 U2	1000 lumens	150h	5 output levels	IP68	122×24mm	72g (2.5oz.)	2*CR123A/1*18650	E-SERIES E35UE
E25UE	Cree XP-L V5	1000 lumens	100h	5 output levels	IP68	161×19.6×25.4mm	87g (3.4oz.)	2*14500/2*AA	E25UE
E20	Cree XP-E2	265 lumens	75h	4 output levels	IP68	154×21×25.4mm	90g (3.2 oz)	2*AA	E20
E15 2016	Cree XP-G2 R5	450 lumens	72h	4 output levels	IP68	64.8×19×22mm	29g	1*16340/1*CR123A	E15 2016
E12	Cree XP-E	130 lumens	36h	3 output levels	IP68	90×19mm	28.5g	1*AA	E12
E05	Cree XP-E2	85 lumens	15h	3 output levels	IP68	66.5×15mm	12.5g	1*AAA	E05
MC-SERIES	Nichia	13 lumens	16h 30min	1 output levels	IP68	71×14.2mm	14g	1*AAA	E01 MC-SERIES
MC11	Cree XP-G2 R5	155 lumens	100h	3 output levels	IP68	99×21.5×25mm	64.8g	1*AA	MC11
FD-SERIES	Gree XI -G2 IX3	100 lumens	10011	σοιραίτονοισ	11 66	33×21.3×25IIIII	0 1.0g	I AA	FD-SERIES
FD41	Cree XP-L HI	900 lumens	150h	4 output levels	IP68	146×25.4×40mm	160g	2*CR123A/1*18650	FD41
FD30	Cree XP-L HI	900 lumens	170h	5 output levels	IP68	140.5×23×25.4mm	96g	2*CR123A/1*18650	FD30
RC/UC-SERIES									RC/UC-SERIES
RC40 2016	Cree XM-L2 U2	6000 lumens	125h	5 output levels	IP68	272×52×108mm		Built-in 7800mAh/7.4V rechargeable Li-ion battery	RC40 2016
RC20	Cree XM-L2 U2	1000 lumens	120h	4 output levels	IP68	161×25.4×40mm	205g	Built-in 2600mAh/3.7V rechargeable Li-ion battery	RC20
RC11 RC09	Cree XM-L2 U2 Cree XM-L2 U2	1000 lumens 550 lumens	150h 56h	5 output levels 4 output levels	IP68 IP68	115.5×23×25.4mm 72×21.5mm	69g 45g	1*18650/2*CR123A 1*16340/1*CR123A	RC11 RC09
RC05	Cree XP-G2 R5	300 lumens	40h	4 output levels	IP68	94x19mm	36.8g	1*14500/1*AA	RC05
UC35	Cree XM-L2 U2	960 lumens	150h	5 output levels	IP68	150×25.4mm	99g	1*18650/2*CR123A	UC35
UC30	Cree XM-L2 U2	960 lumens	120h	4 output levels	IP68	130×25.4mm	77g	1*18650/2*CR123A	UC30
UC02	Cree XP-G2 S2	130 lumens	3h 50min	2 output levels	IP68	43.2×4mm	8g	1*10180	UC02
UC02SS	Cree XP-G2 S2	130 lumens	3h 50min	2 output levels	IP68	43.2×14mm	18.4g	1*10180	UC02SS
UC01	Nichia	45 lumens	50h	3 output levels	IPX6	62×22.5×10mm	13g	Built-in Li-polymer battery	UC01
SD-SERIES	Cree XM-L2 U2 & Cree XQE Red	4000 lumana	7h 200-i-	3 output levels	danuatan 100m	200,020,00	245g	4*CD4224/0*40C50	SD-SERIES
SD20 SD11	Cree XM-L2 U2(Neutral white)	1000 lumens 1000 lumens	7h 30min 3h 40min	3 output levels	underwater 100m underwater 100m	208×26×40mm 138×26×34mm	132.5g	4*CR123A/2*18650 2*CR123A/1*18650	SD20 SD11
3011	Cree AW-L2 O2(Neutral Writte)	1000 lumens	311 40111111	o output levels	underwater 100m	100*20**0411111	102.09	2 CIVI23A/1 10030	3011
HP-SERIES									HP-SERIES
HP40F	Cree XP-E2 M3&XP-G2 R5	450 lumens	280h	8 output levels	IP66	76 × 55.7× 31.5mm	280.5g	4*CR123A/2*18650	HP40F
HP30R	Cree XM-L2 U2&Cree XP-G2 R5	1800 lumens	700h	7 output levels	IP66	77×52×36mm	291g	2*18650	HP30R
HP25R	Cree XM-L2 U2 & XP-G2 R5	1000 lumens	150h	8 output levels	IP66	60×54×32.5mm	183.5g	1*18650/2*CR123A	HP25R
HP15UE	Cree XM-L2	900 lumens	170h	5 output levels 5 output levels	IP66	67.4 × 55.9 × 34.7mm	154.2g	4*AA	HP15UE HP12
HP12 HL-SERIES	Cree XM-L2 U2	900 lumens	145h	3 output levels	IP66	62.1 × 41.2 × 33.3mm	145g	1*18650/2*CR123A	HL-SERIES
HL60R	Cree XM-L2 T6(Neutral white)	950 lumens	100h	6 output levels	IP68	87×46×51mm	121g	1*18650/2*CR123A	HL60R
HL55	Cree XM-L2 T6(Neutral white)	900 lumens	100h	5 output levels	IP68	84 × 46 × 48mm	115g	2*CR123A/1*18650	HL55
HL50	Cree XM-L2 T6(Neutral white)	365 lumens	150h	4 output levels	IP68	63.8 × 32 × 30mm	57g	1*CR123A/1*AA	HL50
HL35	Cree XP-G2 R5	450 lumens	600h	6 output levels	IP66	68.8×45×46mm	120g	2*14500/2*AA	HL35
HL30	Cree XP-G2 R5	230 lumens	160h	5 output levels	IP66	70 × 47.5 × 37.5mm	86.6g	2*AA	HL30
HL26R	Cree XP-G2 R5	500 lumens	150h	6 output levels	IP66	65×44×37mm	86g	Built-in 1600mAh Li-polymer battery	HL26R
HL23	Cree XP-G2 R5	150 lumens	110h	3 output levels	IP68	71 × 38.9 × 40mm	52g	1*AA	HL23
HL15 HL10	Cree XP-G2 R5 Philips LXZ2-5770(Neutral white)	200 lumens 70 lumens	85h 26h	5 output levels 3 output levels	IP67 IP68	63×41.5×35mm 70×25×23mm	60g 33g	1*AA 1*AAA	HL15 HL10
HL05	Imported Premium LED	8 lumens	260h	3 output levels	IP68	36 × 38 × 18mm	13g	2*CR2032	HL05
BICYCLE LIGHT SERIE		- Juniona	20011			oo oo lolliit		Z ONZOCZ	BIKE LIGHT SERIES
BC30R	Cree XM-L2 T6(Neutral white)	1600 lumens	20h 20min	5 output levels	IP66	114 × 50.5 × 31.8mm	221.6g	Built-in 5200mAh/3.7v rechargeable battery	BC30R
BC30	Cree XM-L2 T6	1800 lumens	20h	5 output levels	IP66	126.7 × 50 × 31.8mm	161g	2*18650/4*CR123A	BC30
BT30R	Cree XM-L2 T6(Neutral white)	1800 lumens	22h 35min	5 output levels	IP66	74×50.6×43.5mm	147g	2600mAh/7.4v rechargeable battery pack included	BT30R
BC21R	Cree XM-L2 T6	880 lumens	15h 50min	4 output levels	IP66	113×40.5×42mm	67g	1*18650/2*CR123A	BC21R
CAMP LANTERN SERIES CL30R	Imported Premium Neutral White LED	650 lumens	350h	5 output levels	IP67	93 × 93 × 136mm	412g	3*18650/6*CR123A	CAMP LANTERN SERIES CL30R
CL25R	Imported Premium Neutral White LED	350 lumens	1000h	5 output levels	IP66	52 × 52 × 99mm	130g	1*18650/2*CR123A	CL30R CL25R
CL20	Imported Premium Neutral White LED	165 lumens	24h 5min	5 output levels	IP66	78.4 × 45.2 × 59.1mm	103.2g	2*AA/1*CR123A	CL20
CL05	Imported Premium Tir-colored LED	8 lumens	40h	4 output levels	IP68	72.5×18mm	12.8g	1*AAA	CL05

CUSTOMER SERVICE

Fenix will exert every effort possible to make the service experience for our consumers as memorable, painless and cheerful as possible.

Fenix is concerned about your problems and difficulties when you are using our products, and we will try our best to provide excellent all-round service and support to you via our official website, Customer Service e-mail service and our survey questionnaire.

Fenix Product Warranty Terms

- 1. Service Principle
- a) Fenix provides easy, reliable, speedy service to all lights under our warranty.
- b) Dealers will be responsible for customers' complaints. Customers should contact the dealer/distributor from where they bought their Fenix lights, for warranty support, with their Fenix light Limited's "Warranty Card", or a trade invoice or receipt. Fenix will provide our authorized dealers with the necessary technology and parts to service/repair our lights.
- 2. Warranty Details
- a) 15 days free replacement. Fenix will replace a new product if within 15 days of purchase, any manufacturing defect causes a malfunction during normal use, with the same model. If the model has been discontinued, customer will receive a model with similar specifications, or an improved model.
- b) 5 years free repairs. Fenix offers free repairs for lights for 5 years after date of purchase, if a problem occurs during normal use. Different warranty period for different products:

Туре	Warranty
Flashlight, headlamp, bicycle light and camping lantern (including rechargeable lights but not with built-in battery)	5 years (rechargeable battery excluded)
Flashlight, headlamp, bike light and camping lantern (with built-in battery)	2 years (battery included)
Rechargeable battery, battery charger, bike mount and remote pressure switch	1 year

Fenix products and free offers, except for these listed above, are not covered under the Fenix product warranty.

- c) Limited Lifetime Warranty. For light repairs after expiration of the 5 year free repair warranty period, your light will be repaired but you will be charged for parts. The distributor will provide you with a quote before repairs.
- d) Extended Warranty Service. Fenix recommends that customers register their products with the serial number on the official Fenix website: www.fenixlight.com. Upon successful registration customers will receive an extra six (6) months warranty service.
- e) Warranty Certificate. Customers requesting aftersales service from Fenix distributors or dealers, should present their completed Fenix Warranty Card, purchase invoice or receipt. The distributor should then provide service to the customer/s, and Fenix will support backup for this service.
- f) The free warranty does not cover any damage or failure caused by:
- i. Normal wear and tear;
- ii. Rough operation;
- iii. Battery leakage:
- iv. Any defect or damage caused by improper operation, including but not limited to, operation which does not comply with the warranty or operator's manual specifications, e.g. if the operator's manual warns you against disassembling the flashlight head, doing so may damage the flashlight head and will void the warranty.
- v. Any damage or defect caused by behavior beyond Fenix's control.
- g) To claim against your product warranty, contact our warranty service department with the following information:
- ii. Type and model of product claimed for:
- iii. Serial number;

i. Name:

- iv. Age of the product;
- v. Description of the problem.
- NOTE: This new policy is only valid for flashlights purchased since 01 January 2015.

For any problems/suggestions, please email our Customer Service Department:

service@fenixlight.com (Europe/America regions)

service 1@fenixlight.com (Asia/Oceania/Africa regions)

Tel: +86 400 8866 093

+86 755 2963 1193

The terms of the warranty is subject to change without prior notice. For the latest version, please refer to Fenix's website: www.fenixlight.com. Fenix reserves the rights of modification and final interpretation of these warranty terms.

